

DELL PowerEdge T160 server 2 TB Tower (3U) Intel Xeon 6 6315P 2.8 GHz 16 GB DDR5-SDRAM 300 W

Gamintojas: **DELL** · Modelis: **6TT6G** · EAN: **5397184970126** · Prekės kodas: **717771**



2 761,90 €

Kaina su PVM

Be PVM: **2 282,56 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6315P (12MB Cache, 2.8GHz)
- ✓ 16GB DDR5-SDRAM (1 x 16) & 2000GB HDD
- ✓ iDRAC9, Enterprise 16G



Aprašymas

The single-socket Dell PowerEdge T160 is a small chassis tower server for customers desiring flexibility, affordability and processing power.

Techninė specifikacija

Specifications

Sandėlio grupė Computers [+193][-2216]

Processor

Processor family Intel Xeon 6

Processor manufacturer Intel

Processor model	6315P
Processor frequency	2.8 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	4
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz
Memory	
Internal memory	16 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	Yes
Memory layout (slots x size)	1 x 16 GB
Memory data transfer rate	5600 MT/s
Storage	
Total storage capacity	2 TB
RAID support	No
Optical drive type	No
Number of HDDs installed	1
HDD capacity	2 TB
HDD interface	SATA III
HDD speed	7200 RPM
HDD size	3.5"
Number of HDDs supported	5
Supported HDD sizes	2.5,3.5"
Network	
LAN controller	Broadcom 5720
Ethernet LAN	Yes

Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Design	
Chassis type	Tower (3U)
Product colour	Black
Performance	
Remote administration	iDRAC9, Enterprise 16G
Software	
Operating system installed	No
Compatible operating systems	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Power	
Redundant power supply (RPS) support	No
Power supply	300 W
Number of main power supplies	1
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m
Carbon footprint	
Total carbon footprint (kg of CO2e)	1182
Total carbon emissions, standard deviation (kg of CO2e)	924
Carbon emissions, manufacturing (kg of CO2e)	319.14
Carbon emissions, logistics (kg of CO2e)	130.02
Carbon emissions, energy usage (kg of CO2e)	709.2
Carbon emissions, end-of-life (kg of CO2e)	23.64
PAIA version	Not available

Weight & dimensions

Width	132.5 mm
-------	----------

Height	332.5 mm
--------	----------

Packaging content

Packaging content	European Power Cord 220V
-------------------	--------------------------

Other features

Data transfer rate	6 Gbit/s
--------------------	----------

Bytes per sector	512n
------------------	------

Matmenys ir svoris

Matmenys (l × P × A)	48,00cm × 53,00cm × 32,00cm
----------------------	-----------------------------

Svoris	11,60kg
--------	---------