LG 55UH5Q-E Signage Display Digital signage flat panel 139.7 cm (55") LCD Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS 24/7

Gamintojas: **LG** · Modelis: **55UH5Q-E** · EAN: **8806096522172** · Prekės kodas: **717802**

880,90 €

Kaina su PVM

Be PVM: **728,02 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Digital signage flat panel Black
- ✓ 139.7 cm (55") 3840 x 2160 pixels LCD 500 cd/m²
- ✓ Edge-LED 60 Hz 8 ms
- ✓ Ethernet LAN Wi-Fi
- ✓ Built-in speaker(s) 20 W

Aprašymas

UHD Signage Display with LG webOS Platform and Advanced Security

Superb Picture Quality with Ultra HD Resolution
With the resolution of UHD, it makes the colors and details of the content vivid and realistic. In addition, the wide viewing angle provides clear content.

Even & Slim Bezel Design
The UH5Q series features perfectly balanced horizontal and vertical slim bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience.

Convenient webOS Platform

The UH5Q is equipped with a high-performance SoC that allows for multiple tasks to be performed without a separate media player. The webOS platform provides app development tools with an intuitive UI that enhances user convenience, and includes webOS partner apps to create an SI-friendly environment.

* SoC : System On Chip
** SI : System Integrator

Design for Space Utilization
Designed with thin bezels and simple cable management, the UH5Q saves space. With specialized hidden power inlets, it can be installed close to the wall, leaving only about 13.5 mm of space with the slim bracket.

* The product image will differ slightly from the actual appearance of the product due to the variance caused by each inch option.

Durability that Provides Reliability
Optimized for business environments, the UH5Q is protected against salt, dust, iron powder and humidity thanks to conformal partial coating on power board, allowing for stable operation. Also, its customer-centric features, such as IP5x and Shock Monitoring*, provide both reliability and satisfaction.

* When a physical impact occurs on the product, an alert is provided to the administrator through the media controller.

Comprehensive Security
webOS Signage goes beyond security measures at the operating system (OS) level. LG Shield employs a five-tiered defense system, encompassing server, application, operating system, system, and hardware. Each layer operates independently, providing comprehensive protection against various threats. Also webOS platform support ETSI EN 303 645.

SuperSign Solutions
SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

* SuperSign must be purchased separately.

Techninė specifikacija

Specifications	
Sandėlio grupė	Signage Displays [+40][-211]
Display	
Display diagonal	139.7 cm (55")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	ADS
LED backlight	Yes

LED backlighting type	Edge-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Panel life	50000 h
Colour depth	10 bit
Native refresh rate	60 Hz
Colour gamut	95%
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
DisplayPorts quantity	1
USB port	Yes
HDMI input ports quantity	3
DisplayPorts in	1
USB ports quantity	2
USB version	2
USB connector type	USB Type-A
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
Remote (IR) input	1
PC Audio out	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Orientation	Horizontal/Vertical
Panel mounting interface	300 x 300 mm
Bezel colour	Black
Performance	
Purpose	Universal
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes
Number of OSD languages	21
Operating hours (hours/days)	24/7
HDCP	Yes
Smart modes	Energy saving
Automatic brightness control	Yes
International Protection (IP) code	IP5X
HDCP version	1.4/2.2
Power	
Power consumption (typical)	130 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
Power consumption (max)	154 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	103 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Heat dissipation	351 BTU/h
Computer system	
Computer system	Yes
Computer system type	System on Chip (SoC)
Internal memory	16 GB
Operating system installed	WebOS
Operating system version	webOS 8.0
Weight & dimensions	
Display width	1240.1 mm
Display depth	29.7 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Display height	711.9 mm
Display weight	14.3 kg
Packaging data	
Package width	1360 mm
Package depth	152 mm
Package height	810 mm
Package weight	18.1 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Certificates	
Certification	CB / NRTL / FCC Class "B" / CE / KC
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Security algorithms	SNMP
Features	
Heat dissipation (max)	525 BTU/h
Technical details	
Sustainability certificates	ENERGY STAR, ErP
Surface treatment	25%
Real Time Clock (RTC)	Yes
Other features	
Power consumption (PowerSave)	72 W
Built-in brightness sensor	Yes
Power supply type	Internal
Bezel width	1.14 cm
Plug and Play	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	81,00cm × 135,00cm × 15,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Svoris	18,00kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903