


LG 32UL5Q-M Signage Display Digital signage flat panel 81.3 cm (32") LCD Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS 24/7

Gamintojas: **LG** · Modelis: **32UL5Q-M** · EAN: **8806096729892** · Prekės kodas: **717886**



529,90 €

Kaina su PVM

Be PVM: **437,93 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Resolution : 3,840 × 2,160 (UHD)
- ✓ Brightness : 500 nit (Typ.)
- ✓ 24Hr Usage Scene (24 Hours / 7 Days)
- ✓ Even Bezel
- ✓ High-Performance with webOS 6.1



Aprašymas

LG webOS UHD Signage for 24/7 Operation

Superb Picture Quality with Ultra HD Resolution

The UL5Q-M series, with UHD resolution, enhances the realism of colors and details in the content. Its wide viewing angle offers clear visuals, while its 500-nit brightness vividly showcases the content.

High-Performance with LG webOS 6.1

LG webOS 6.1 is available on the UL5Q-M series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI*.

Even Bezel Design

The UL5Q-M series features even bezels, enhancing the aesthetic appeal of various spaces. These uniform bezels not only facilitate easy installation but also transform standard displays into elegant focal points.

Adaptive Viewing Experience

Experience the flexibility with the UL5Q-M series' up/down tilt capability. Whether mounted high or low, the display can be adjusted to eye level, offering viewer engagement regardless of installation height. This versatility not only enhances spatial efficiency but also provides visual comfort, delivering clear information from various viewing angles.

Engineered for 24/7 Operation

Built for environments that never sleep, the UL5Q-M series features panel technology that enables 24/7 operation.

* The UL5Q-M series includes the same standard warranty period as other signage models and offers an optional extended warranty, providing coverage for up to 5 years in total. If the extended warranty is purchased, coverage ends when either 50,000 hours of usage is reached or the 5-year period expires, whichever comes first.

Built-In Brightness Sensor

The UL5Q-M series' front-mounted brightness sensor automatically adjusts brightness to match various lighting conditions, optimizing viewing quality and energy efficiency without manual intervention. This adaptive feature offers consistent display performance while also supporting power optimization, delivering a visual experience that dynamically responds to environmental changes.

Advanced Security Architecture

The UL5Q-M series incorporates LG's Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today's challenging security landscape.

Remote Monitoring and Control

This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anytime, anywhere from their mobile phone & PC in a network-accessible environment, with access to both current and past data. It allows the user to monitor the unit, make adjustments, and control the unit remotely in real time.

EPEAT Registered

The Electronic Product Environmental Assessment Tool (EPEAT) is a method for several layers of customers to evaluate the effect of a product on the environment. UL5Q-M series is an EPEAT Bronze-certified* display which means that it meets all the required criteria in the Computers and Displays category.

LG ConnectedCare

Maintenance is easy and fast with the optional LG ConnectedCare* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses.

* The availability of the 'LG ConnectedCare' service differs by region, and it needs to be purchased separately. So please contact the LG sales representative in your region for more details.

Techninė specifikacija

Specifications	
Sandėlio grupė	Signage Displays [+40][–211]
Display	
Display diagonal	81.3 cm (32")

Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	VA
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	4000:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Colour saturation	80%
Rated lifetime	50000 h
Native refresh rate	60 Hz
Haze rate	1%
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
USB port	Yes
HDMI version	2.2/1.4
USB ports quantity	2
USB version	2
USB connector type	USB Type-A
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
PC Audio out	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black

Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	200 x 200 mm
Bezel width (bottom)	1.19 cm
Bezel width (side)	1.19 cm
Bezel width (top)	1.19 cm
Bezel colour	Black
Performance	
Purpose	Commercial
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Operating hours (hours/days)	24/7
Web browser	Yes
webRTC support	Yes
Power	
Power consumption (typical)	44 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
Power consumption (max)	85 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Internal memory	8 GB
Operating system installed	WebOS
Operating system version	6.1
Weight & dimensions	
Display width	725.2 mm
Display depth	65 mm
Display height	420.1 mm
Display weight	5.4 kg
Packaging data	
Package width	825 mm
Package depth	525 mm

Package height	135 mm
Package weight	7.2 kg
Packaging content	
Remote control included	Yes
Cables included	Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Sensors	
Gyroscope	Yes
Temperature sensor	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Technical details	
Compliance certificates	CB, CE, Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC)
Other features	
Power supply type	Internal
Matmenys ir svoris	
Matmenys (I × P × A)	104,00cm × 15,00cm × 68,00cm
Svoris	12,80kg