

iiyama TE5513A-B3AG Signage Display Interactive flat panel 138.7 cm (54.6") LCD Wi-Fi 500 cd/m² 4K Ultra HD Black Touchscreen Built-in processor Android 24/7

Gamintojas: **IIYAMA** · Modelis: **TE5513A-B3AG** · EAN: **4948570128105** · Prekės kodas: **717889**



1 456,90 €

Kaina su PVM

Be PVM: **1 204,05 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Interactive flat panel Black
- ✓ Ethernet LAN Wi-Fi
- ✓ 138.7 cm (54.6") 3840 x 2160 pixels LCD 500 cd/m²
- ✓ Built-in speaker(s) 60 W
- ✓ Touchscreen 60 Hz 8 ms



Aprašymas

The TE5513A-B3AG is a 4K UHD Google EDLA Certified interactive display that redefines performance and precision. Featuring a Zero-Gap Air Bonding LCD screen to eliminate parallax and with PureTouch-IR+ with Palm Rejection, it ensures smooth, accurate interaction. Powered by iiWare 21E with Android 14-EDLA, WiFi-6E with BT 5.0 connectivity, iiControl (DMS), iiShare and integrated EShare app (wireless screen sharing), it integrates seamlessly into your ecosystem. Enjoy added features like a PIR motion sensor for energy efficiency; perfect for workplaces and educational spaces, it fosters collaboration, communication, and progress.

Techninė specifikacija

Specifications	
Sandėlio grupė	Signage Displays [+40][[-211]
Display	
Display diagonal	138.7 cm (54.6")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	Yes
Panel type	IPS
Touchscreen technology	PureTouch-IR
Number of simultaneous touchpoints	40
Multi-touch	Yes
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.315 x 0.315 mm
Active display area (W x H)	1209.6 x 680.4 mm
Display diagonal (metric)	138.8 cm
Colour saturation	72%
Horizontal scan range	30 - 135 kHz
Native refresh rate	60 Hz
Surface hardness	7H
Touch response time	5 ms
Glass thickness	3.2 mm
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
DisplayPorts quantity	1
USB port	Yes
HDMI version	2
HDMI input ports quantity	1
HDMI output ports quantity	1

Consumer Electronics Control (CEC)	Yes
DisplayPort version	1.2
USB ports quantity	6
USB version	3.2 Gen 1 (3.1 Gen 1)
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
Ethernet LAN (RJ-45) ports	2
RS-232 interface	Yes
RS-232C	Yes
OPS module slot	Yes
Audio Return Channel (ARC)	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	60 W
Design	
Product design	Interactive flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal
Panel mounting interface	400 x 400 mm
Bezel width (bottom)	4.67 cm
Bezel width (side)	1.67 cm
Bezel width (top)	1.41 cm
Bezel colour	Black
Anti-glare screen	Yes
Performance	
Purpose	Commercial
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	CAT, Czech, Danish, German, English, Spanish, Estonian, Finnish, French, Hungarian, Italian, Lithuanian, LAT, Norwegian, Dutch, Polish, Russian, Swedish, Ukrainian
Operating hours (hours/days)	24/7
HDCP	Yes
HDCP version	2.2

Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	126 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	G
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Computer system	Yes
Built-in processor	Yes
Computer system type	System on Chip (SoC)
Processor manufacturer	Rockchip
Processor family	ARM Rockchip
Processor model	RK3576
Processor architecture	ARM Cortex-A53+Cortex-A72
Processor cores	8
Internal memory	6 GB
On-board graphics card model	ARM Mali-G52
Internal storage capacity	128 GB
Operating system installed	Android
Operating system version	14
Weight & dimensions	
Display width	1267 mm
Display depth	117.5 mm
Display height	765.5 mm
Display weight	28.7 kg
Width	1267 mm
Depth	117.5 mm
Height	765.5 mm
Weight	28.7 kg
Packaging data	
Package width	1385 mm
Package depth	185 mm

Package height	865 mm
Package weight	34.8 kg
Packaging content	
Remote control included	Yes
Stylus pen	Yes
Number of stylus pens	4
Cables included	AC, USB, HDMI
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Logistics data	
Products per pallet	6 pc(s)
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Ethernet LAN data rates	1000 Mbit/s
Wi-Fi standards	Wi-Fi 6 (802.11ax)
Technical details	
OPS slot	1
Sustainability certificates	ErP
Warranty period	5 year(s)
Compliance certificates	CB, CE, EAC, REACH, RoHS, TÜV mark, WEEE
Audio in (mini jack)	Yes
Playback media	Y
User controls	general settings (input, volume, backlight), audio (volume, bass, treble, balance, sound mode, mute), screen settings (aspect ratio, pixel shift), display settings (brightness, contrast, hue, display mode colour temp), settings (wireless & networks, share, device, personal, system)
Other features	
Quick start guide	Yes
Bluetooth version	5
Brightness	500 cd/m²
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Power supply type	Internal
Matmenys ir svoris	

Matmenys (I × P × A)	87,00cm × 138,00cm × 19,00cm
Svoris	34,80kg