

Hikvision DS-7604NXI-K1/VPro 4-Channel NVR AcuSeek

Gamintojas: **HIKVISION** · Modelis: **DS-7604NXI-K1/VPro** · EAN: **6936422186012** · Prekės kodas: **717923**

198,90 €

Kaina su PVM

Be PVM: 164,38 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

ADVANCED AI-POWERED SURVEILLANCE WITH ACUSENSE TECHNOLOGY

The Hikvision 4-ch 1U AcuSeek K VPro NVR utilizes cutting-edge AcuSense technology to enhance security monitoring. This system minimizes manual effort and reduces security costs by effectively distinguishing between genuine threats and false alarms. With features like facial recognition, perimeter protection, and motion detection 2.0, it ensures accurate surveillance, allowing for a more efficient response to potential security breaches.

IMPRESSIVE DECODING CAPABILITIES FOR HIGH-QUALITY VIDEO

This NVR supports up to 4 channels of high-definition video decoding, accommodating resolutions of 12 MP, 8 MP, 4 MP, and 2 MP. With a decoding capacity of up to 40 Mbps incoming bandwidth, it delivers smooth and clear video playback. The device is compatible with various video formats, including H.265+/H.265/H.264+/H.264, ensuring flexibility and high-quality output for diverse surveillance needs.

ROBUST STORAGE AND CONNECTIVITY OPTIONS

Designed for extensive storage, the Hikvision NVR supports a single SATA interface with a capacity of up to 16 TB for each HDD. This allows for substantial video data retention, essential for comprehensive surveillance. Additionally, it features a 10/100/1000 Mbps self-adaptive Ethernet interface, enabling seamless network connectivity and remote access for real-time monitoring and management.

USER-FRIENDLY INTERFACE WITH MULTI-LANGUAGE SUPPORT

The NVR is equipped with a user-friendly graphical interface that supports multiple languages, including English, Russian, and many others. This feature enhances accessibility for users across different regions, making it easier to navigate through settings and configurations. The independent HDMI and VGA outputs provide flexible display options, ensuring compatibility with various monitor setups.

DURABLE DESIGN FOR VERSATILE ENVIRONMENTAL CONDITIONS

Built to withstand a range of environmental conditions, the Hikvision NVR operates effectively in temperatures from -10 °C to 55 °C (14 °F to 131 °F) and humidity levels of 10 to 90%. Its compact dimensions (319 mm × 239 mm × 48 mm) and lightweight design (≤ 1.2 kg) make it suitable for various installation scenarios, whether in commercial or residential settings. The device also meets multiple international certifications, ensuring reliability and safety.

Techninė specifikacija

Specifications	
Sandėlio grupė	without Category [+99][-2182]