

## Conceptronic ALTHEA10W

Gamintojas: **CONCEPTRONIC** · Modelis: **ALTHEA10W** · EAN: **4015867230862** · Prekės kodas: **718546**



**15,90 €**

Kaina su PVM

Be PVM: **13,14 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ **Dedicated Port Connector:** Equipped with a USB-C ports (with PD 3.0), providing up to 25W of total power and high-speed charging for a wide range of devices with varying power requirement.
- ✓ **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ **Wide Compatibility:** Supports a range of output options from 3.3V to 12.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ **Efficiency and Fast Charging Technology:** Incorporates USB Power Delivery (PD) 3.0 for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize charging efficiency and minimize heat generation.



### Aprašymas

The ALTHEA10W USB-C charger offers efficient and fast charging, featuring a USB Type-C port with Power Delivery (PD) technology that automatically detects and charges devices such as Samsung Galaxy S21/S20/Note10/Note20, Nintendo Switch, iPad, iPhone etc., at up to 25W speed. The charger is protected against overload, short circuiting and overheating, and with a compact and light-weight design, it is a great travel device and daily companion.

### Techninė specifikacija

**Specifications**

Sandėlio grupė Notebook Chargers [+263][-61]

**Performance**

Charger type Indoor

Charger compatibility Universal

Power source type AC

Number of simultaneously connected devices (max) 1

USB Type-C ports quantity 1

Fast charging Yes

Fast charging technology Power Delivery 3.0

USB Power Delivery (USB PD) Yes

USB Power Delivery revision 3

Power protection features Overheating, Overload, Short circuit

**Design**

Product colour White

**Power**

Input voltage 100 - 240 V

Input frequency 50 - 60 Hz

Input current 0.6 A

Maximum power 25 W

Maximum output voltage 3.3 V

Minimum output voltage 12 V

Output current (5V) 3 A

Output current (9V) 2.77 A

Output current (12V) 2.1 A

Power consumption (no load) 0.1 W

**Weight & dimensions**

Width 40 mm

Depth 43 mm

Height 25 mm

Weight 54 g

**Packaging data**

Package width 70 mm

Package depth 70 mm

|                                   |             |
|-----------------------------------|-------------|
| Package height                    | 30 mm       |
| Package weight                    | 30 g        |
| Package type                      | Box         |
| Operational conditions            |             |
| Operating temperature (T-T)       | 0 - 40 °C   |
| Storage temperature (T-T)         | -20 - 80 °C |
| Operating relative humidity (H-H) | 10 - 80%    |
| Storage relative humidity (H-H)   | 5 - 95%     |
| Packaging content                 |             |
| Manual                            | Yes         |
| Certificates                      |             |
| Compliance certificates           | CE, RoHS    |
| Logistics data                    |             |
| Pallet net height                 | 170 cm      |
| Pallet net length                 | 80 cm       |
| Pallet net width                  | 120 cm      |
| Harmonized System (HS) code       | 8504408390  |
| Pallet gross width                | 120 cm      |
| Pallet gross length               | 80 cm       |
| Pallet gross height               | 170 cm      |
| Master (outer) case width         | 320 mm      |
| Master (outer) case length        | 220 mm      |
| Master (outer) case height        | 375 mm      |
| Master (outer) case gross weight  | 8.7 kg      |
| Products per master (outer) case  | 100 pc(s)   |
| Country of origin                 | China       |
| Sustainability                    |             |
| Sustainability compliance         | Yes         |