

LevelOne Gigabit Ethernet over VDSL2

Gamintojas: **LEVEL ONE** · Modelis: **VDS-2201** · EAN: **4015867238387** · Prekės kodas: **718630**



254,90 €

Kaina su PVM

Be PVM: **210,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports a VDSL connection up to 2km over single pair copper wire
- ✓ Provides 150Mbps downstream and 60Mbps
- ✓ Selectable fixed data rate and fixed SNR margin
- ✓ Features selectable Fast and Interleaved modes
- ✓ Low-Latency for Video/Voice/Data applications



Aprašymas

VDS-2201 is an Industrial Ultra-Speed VDSL2 Extender that supports VDSL2 profile 35b/30a/17a with a remarkable aggregated bandwidth of over 300Mbps. It delivers fiber optic-like speeds on existing copper infrastructure, enabling a good alternative in the place where fiber is not economical to deploy. VDS-2201 is equipped with a Gigabit Ethernet port (RJ45 connector) and one VDSL2 port (RJ45 connector) in the metal enclosure for easy installation in a hardened environment. The symmetric configuration can be applied as a long-reach Ethernet connection up to 3,000 meters, while an Asymmetric configuration can be used for other services like video streaming or IP surveillance services which require high traffic flow in a uni-direction configuration

Techninė specifikacija

Specifications

Sandėlio grupė

I/O Cards & Adapters [+365][122]

Network

Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Maximum transfer distance	3000 m
---------------------------	--------

Features

Internal	No
Plug and Play	Yes
LED indicators	Yes
Product colour	Black
Housing material	Metal

Ports & interfaces

Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
RJ-11 ports quantity	1
Terminal block included	Yes

Power

Output voltage	12 - 24 V
Power consumption (typical)	4.5 W
Power over Ethernet (PoE)	Yes

Weight & dimensions

Width	94.5 mm
Depth	72.5 mm
Height	23 mm
Weight	220 g

Operational conditions

Operating temperature (T-T)	-20 - 65 °C
Storage temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	0 - 95%

Packaging data

Package width	143 mm
---------------	--------

Package depth	132 mm
Package height	92 mm
Package weight	350 g
Package type	Box
Certificates	
Compliance certificates	CE, UKCA
Logistics data	
Country of origin	Taiwan
Pallet gross length	100 cm
Pallet gross width	120 cm
Pallet gross height	149 cm
Customs product code (TARIC)	8517620000
Harmonized System (HS) code	8517620000
Master (outer) case width	434 mm
Master (outer) case length	307 mm
Master (outer) case height	482 mm
Master (outer) case gross weight	11.7 kg
Products per master (outer) case	30 pc(s)