

# Lindy USB 2.0 Low Profile Type A to C Adapter

Gamintojas: **LINDY** · Modelis: **41884** · EAN: **4002888418843** · Prekės kodas: **719030**



**8,91 €**

Kaina su PVM

Be PVM: **7,36 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Connects a USB Type C cable to a USB Type A device
- ✓ Backwards compatible with USB 1.1 and 1.0 devices
- ✓ Ultra compact size, perfect for use when travelling or in discreet installations
- ✓ Supports USB data transfer speeds up to 480Mbps
- ✓ 10 year warranty



## Aprašymas

USB adapters allow users to connect different USB interfaces to a device that uses a differing USB port.

The Lindy USB Type A to C Adapter allows users to connect a USB Type C cable to a USB Type A device such as a PC or laptop. It's ultra compact design makes this adapter perfect for taking to meetings-on-the-go or leaving in conference rooms for future use. Due to it's ultra low profile, it does not put any strain on the port and does not block any other ports.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

## Techninė specifikacija

**Specifications**

|                |                      |
|----------------|----------------------|
| Sandėlio grupė | USB Hubs [+541][-77] |
|----------------|----------------------|

**Ports & interfaces**

|                            |             |
|----------------------------|-------------|
| Connector 1                | USB Type-A  |
| Connector 2                | USB Type-C  |
| Connector 1 gender         | Male        |
| Connector 2 gender         | Female      |
| Connector 1 form factor    | Straight    |
| Connector 2 form factor    | Straight    |
| USB version                | 2           |
| Connector contacts plating | Nickel/Gold |

**Performance**

|                     |             |
|---------------------|-------------|
| Product colour      | Black       |
| Housing material    | Aluminium   |
| Connector material  | Copper      |
| Conductor material  | Copper      |
| Data transfer rate  | 0.48 Gbit/s |
| Connector shielding | No          |
| Plug and Play       | Yes         |

**Operational conditions**

|                             |             |
|-----------------------------|-------------|
| Operating temperature (T-T) | -25 - 85 °C |
| Storage temperature (T-T)   | -25 - 85 °C |
| Relative humidity           | 0 - 80%     |

**Certificates**

|               |             |
|---------------|-------------|
| Certification | RoHS, REACH |
|---------------|-------------|

**Weight & dimensions**

|        |         |
|--------|---------|
| Width  | 14.9 mm |
| Depth  | 2.5 mm  |
| Height | 6.9 mm  |

**Packaging content**

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

**Packaging data**

|              |         |
|--------------|---------|
| Package type | Polybag |
|--------------|---------|