

Lindy USB Type C to DisplayPort 4K144 Converter

Gamintojas: **LINDY** · Modelis: **43269** · EAN: **4002888432696** · Prekės kodas: **719126**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Converts a USB Type C port to an DP port
- ✓ Supports DP resolutions up to 4K 3840x2160@144Hz
- ✓ Requires DisplayPort Alternate Mode support by the USB Port/Bus
- ✓ Plug and Play, no drivers required
- ✓ 2 year warranty



Aprašymas

The Lindy USB Type C to DisplayPort Converter allows users to easily add external video capabilities to a computer featuring the USB Type C port with support for DisplayPort Alternate Mode. The converter is powered by the USB Bus, therefore no external power supply is needed, saving space and time when connecting.

With support for resolutions up to 3840x2160 144Hz, content can be viewed with superior clarity and stunning accuracy, while the Type C connectors reversible design means a connection can be found regardless of which way the cable is inserted into the port of a laptop, notebook or Macbook.

With Plug and Play installation, this converter can be installed with minimum fuss, perfect for both professional and first time users.

Techninė specifikacija

Specifications	
Sandėlio grupė	I/O Cards & Adapters [+365][-122]
Performance	
DVI output	No
HDMI output	No
DisplayPort output	Yes
Number of displays supported	1
USB connector type	USB Type-C
USB connector gender	Male
USB connector form factor	Straight
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
HDCP version	2.2
DisplayPort version	1.4
Maximum resolution	3840 x 2160 pixels
Refresh rate at maximum resolution	144 Hz
Supported graphics resolutions	3840 x 2160
Chipset	LT87101CD
Data transfer rate (max)	32.4 Gbit/s
Certification	CE, FCC, RoHS, REACH, CP65
Design	
Product colour	Black
Housing material	Acrylonitrile butadiene styrene (ABS), Plastic
Weight & dimensions	
Width	45 mm
Depth	45 mm
Height	15 mm
Weight	30 g
USB cable length	0.21 m
Operational conditions	
Operating temperature (T-T)	-20 - 40 °C
Storage temperature (T-T)	-40 - 80 °C
Operating relative humidity (H-H)	10 - 85%
Packaging data	
Package width	174 mm

Package depth	194 mm
---------------	--------

Package weight	39 g
----------------	------

Technical details

Compliance certificates	CE, RoHS, REACH
-------------------------	-----------------