

Conceptronic DONN29G 6-in-1 USB 3.2 Gen 2 Docking Station, 4K60Hz HDMI, USB-A 10Gbps x 2, USB-C 10Gbps, GbE LAN, 140W USB PD 3.1

Gamintojas: **CONCEPTRONIC** · Modelis: **DONN29G** · EAN: **4015867239629** · Prekės kodas: **719140**



53,91 €

Kaina su PVM

Be PVM: **44,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6-in-1 USB-C to HDMI/USB-C PD/USB-A (10Gbps)/USB-C (10Gbps)/GbE multiport adapter
- ✓ Supports HDMI resolutions up to 4K 60Hz
- ✓ Supports USB Power Delivery (PD) 3.1 up to 140W
- ✓ Provides a Gigabit Ethernet port with speeds up to 1000Mbps
- ✓ Supports Wake-on-LAN feature to startup computers remotely
- ✓ USB 3.2 Gen 2 SuperSpeed (10Gb/s)
- ✓ Multi-platform support: Windows, macOS, ChromeOS, Linux, Android, iOS
- ✓ Simple Plug and Play installation
- ✓ Cable length: 25cm
- ✓ Aluminum casing for heat dissipation



Aprašymas

This 6-in-1 Docking Station expands your device's USB Type-C functionality with HDMI, USB-C PD, USB-C (10Gbps), USB-A (10Gbps), and RJ45 ports. It's an ideal solution for MacBooks or Windows laptops with built-in wireless connectivity but no Ethernet port. Featuring a Gigabit Ethernet connection, it ensures fast and reliable wired network access. Additionally, the docking station supports up to 140W power delivery for compatible laptops or tablets with USB-C PD 3.1 support.

The docking station enables USB-C-compatible laptops, tablets, or smartphones to connect to an HDMI-enabled display, delivering stunning 4K Ultra HD resolution at a 60Hz refresh rate. With data transfer speeds of up to 10Gbps, it ensures stable and efficient performance, making it ideal for home entertainment, office presentations, and classroom teaching.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook Docks [+118][-14]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 2.0 ports quantity	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	0
HDMI ports quantity	1
Microphone in	No
Headphone outputs	0
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3.1
USB Power Delivery up to	140 W
HDMI version	2
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN ready	Yes
Networking standards	IEEE 802.3ab
Performance	
Product colour	Grey
Card reader integrated	No
Data transfer rate	10 Gbit/s
Plug and Play	Yes
Housing material	Aluminium
Country of origin	China
Power	

Power source type	USB
USB cable length	0.25 m
Software	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Mobile operating systems supported	Android 10.0, Android 11.0, Android 12.0, Android 13.0, Android 14.0, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 8.1, Android 9.0
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Weight & dimensions	
Width	131.5 mm
Depth	32.5 mm
Height	14 mm
Weight	60 g
Packaging data	
Package width	173 mm
Package depth	23 mm
Package height	75 mm
Package weight	80 g
Packaging content	

Quick start guide	Yes
-------------------	-----

Technical details

Compliance certificates	CE, RoHS
-------------------------	----------

Logistics data

Products per master (outer) case	100 pc(s)
----------------------------------	-----------

Master (outer) case width	460 mm
---------------------------	--------

Master (outer) case length	395 mm
----------------------------	--------

Master (outer) case height	195 mm
----------------------------	--------

Master (outer) case gross weight	8.8 kg
----------------------------------	--------

Harmonized System (HS) code	8471800000
-----------------------------	------------

Pallet gross width	120 cm
--------------------	--------

Pallet gross length	80 cm
---------------------	-------

Pallet gross height	171.2 cm
---------------------	----------

Other features

Master (outer) cases per pallet	32 pc(s)
---------------------------------	----------