

Conceptronic ALTHEA20W45 2-Port 45W GaN USB PD Charger, USB-C x 1, USB-A x 1, QC 3.0, PPS, PD 3.0

Gamintojas: CONCEPTRONIC · Modelis: ALTHEA20W45 · EAN: 4015867240717 · Prekės kodas: 719141



26,90 €

Kaina su PVM

Be PVM: 22,23 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High-Power GaN Technology: This charger utilizes advanced Gallium Nitride (GaN) technology, providing up to 45W of total power for faster and more efficient charging.
- ✓ Versatile Port Selection: Equipped with 2 ports including 1 USB-C ports (with PD 3.0) and 1 USB-A ports (with QC 3.0), allowing simultaneous charging for multiple devices with varying power requirements.
- ✓ Wide Compatibility: Supports a range of output options from 5.0V to 20.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ Enhanced Safety Features: Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ Efficiency and Fast Charging Technology: Incorporates USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize charging efficiency and minimize heat generation.



Aprašymas

This charger leverages advanced Gallium Nitride (GaN) technology to provide up to 45W of total power, delivering faster and more efficient charging. It features a versatile port selection with 1 USB-C port supporting USB Power Delivery (PD) 3.0 and 1 USB-A port with Quick Charge (QC) 3.0, allowing for simultaneous charging of multiple devices with different power needs. The charger supports a wide range of output options from 5.0V to 20.0V, ensuring compatibility with a variety of devices, including smartphones and laptops. Enhanced safety is ensured with built-in

protections against overload, short circuiting, and overheating. Additionally, it incorporates USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize efficiency and minimize heat generation.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook Chargers [+263][-61]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB Type-C ports quantity	1
Fast charging	Yes
Fast charging technology	Power Delivery 3.0, Programmable Power Supply (PPS), Quick Charge 3.0
Programmable power supply (PPS)	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
Power protection features	Overheating, Overload, Short circuit
Design	
Product colour	White
Housing material	Polycarbonate (PC)
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	1.2 A
Maximum power	45 W
Maximum output voltage	20 V
Minimum output voltage	5 V
Port 1 output current	3 A
Port 2 output current	3 A
Weight & dimensions	
Width	57 mm
Depth	51 mm

Height	32 mm
Weight	86.5 g
Packaging data	
Package width	127 mm
Package depth	84 mm
Package height	35 mm
Package weight	134.5 g
Package type	Hanging box
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 80 °C
Storage relative humidity (H-H)	10 - 90%
Packaging content	
Manual	Yes
Certificates	
Compliance certificates	CE, RoHS
Technical details	
Master (outer) cases per pallet	32 pc(s)
Logistics data	
Customs product code (TARIC)	8504408390
Harmonized System (HS) code	850440
Pallet gross width	120 cm
Pallet gross length	80 cm
Pallet gross height	159.2 cm
Master (outer) case width	385 mm
Master (outer) case length	272 mm
Master (outer) case height	360 mm
Master (outer) case gross weight	11.5 kg
Products per master (outer) case	80 pc(s)
Country of origin	China
Matmenys ir svoris	
Svoris	0,13kg