

Lindy 4 Port USB 3.0 Hub with On/Off Switches

Gamintojas: **LINDY** · Modelis: **43309** · EAN: **4002888433099** · Prekės kodas: **719274**



22,91 €

Kaina su PVM

Be PVM: **18,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Allows 4 USB 3.0 devices to be connected to a single port
- ✓ On/Off switch on each port allows users to manage power consumption of the connected devices
- ✓ SuperSpeed transfer rates up to 5Gbps, backwards compatible with USB 2.0 / 1.1
- ✓ Bus-powered with optional USB Micro-B socket for use with high powered devices
- ✓ 2 year warranty



Aprašymas

A USB hub connects to a PC or laptop and provides additional USB ports for connecting multiple peripherals or other devices simultaneously.

The Lindy 4 Port USB 3.0 Hub provides convenient access and effective power management for USB peripherals and storage devices. Capable of data transfer speeds of up to 5Gbps, the hub is also backwards compatible with USB 2.0 and 1.1.

The hubs individual On/Off switching ports can help reduce overall power consumption and are perfect for accessing external hard drives or other periodically used devices. An optional power supply can be connected for use with high current USB devices.

Techninė specifikacija

Specifications

Sandėlio grupė USB Hubs [+541][-77]

Ports & interfaces

Ports quantity 4

Host interface USB 3.2 Gen 1 (3.1 Gen 1) Type-A

Hub interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 4

Features

Data transfer rate 5 Mbit/s

Product colour Grey

Housing material Acrylonitrile butadiene styrene (ABS), Aluminium, Polycarbonate (PC)

Power

Power supply type USB

Input voltage 5 V

Weight & dimensions

Width 100 mm

Depth 30 mm

Height 9 mm

Weight 42 g

Packaging data

Package width 174 mm

Package depth 194 mm

Package height 15 mm

Package weight 60 g

Packaging content

Cables included USB Type-A to USB Type-B

Manual Yes

Operational conditions

Operating temperature (T-T) 0 - 50 °C

Operating temperature (T-T) 32 - 122 °F

Storage temperature (T-T) 0 - 60 °C

Operating relative humidity (H-H) 0 - 85%

Logistics data

Harmonized System (HS) code 84719000