

Conceptronic ALTHEA07W 1-Port 20W USB-C PD Charger

Gamintojas: **CONCEPTRONIC** · Modelis: **ALTHEA07W** · EAN: **4015867230046** · Prekės kodas: **719424**



14,90 €

Kaina su PVM

Be PVM: 12,31 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Dedicated Port Connector:** Equipped with a USB-C ports (with PD 3.0), providing up to 20W of total power and high-speed charging for a wide range of devices with varying power requirement.
- ✓ **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ **Wide Compatibility:** Supports a range of output options from 5.0V to 12.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ **Efficiency and Fast Charging Technology:** Incorporates USB Power Delivery (PD) 3.0 technology for efficient and rapid charging, ensuring broad device compatibility.



Aprašymas

This charger is equipped with a dedicated USB-C port featuring Power Delivery (PD) 3.0, providing up to 20W of total power for high-speed charging across a wide range of devices. It supports a range of output options from 5.0V to 12.0V, ensuring compatibility with devices from smartphones to laptops. Enhanced safety features include built-in protections against overload, short-circuiting, and overheating, ensuring the safety of both the charger and connected devices. Incorporating USB Power Delivery (PD) 3.0 technology, this charger ensures efficient and rapid charging, offering broad device compatibility.

Techninė specifikacija

Specifications

Sandėlio grupė	Notebook Chargers [+263][-61]
----------------	-------------------------------

Performance

Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
USB Type-C ports quantity	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3

Design

Product colour	White
----------------	-------

Power

Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Maximum power	20 W
Maximum output voltage	5 V
Minimum output voltage	12 V
Output current (5V)	3 A
Output current (9V)	2.22 A
Output current (12V)	1.67 A

Weight & dimensions

Width	40 mm
Depth	44 mm
Height	26 mm
Weight	55 g

Packaging data

Package width	30 mm
Package depth	100 mm
Package height	70 mm
Package weight	70 g
Package type	Box

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 80 °C

Operating relative humidity (H-H)	10 - 80%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Manual	Yes
--------	-----

Logistics data

Harmonized System (HS) code	8504408390
-----------------------------	------------

Pallet gross width	120 cm
--------------------	--------

Pallet gross length	80 cm
---------------------	-------

Pallet gross height	170 cm
---------------------	--------

Master (outer) case width	290 mm
---------------------------	--------

Master (outer) case length	360 mm
----------------------------	--------

Master (outer) case height	460 mm
----------------------------	--------

Master (outer) case gross weight	11.2 kg
----------------------------------	---------

Products per master (outer) case	100 pc(s)
----------------------------------	-----------

Country of origin	China
-------------------	-------