

# LevelOne RJ45 to SC Managed Fast Ethernet Media Converter, Multi-Mode Fiber

Gamintojas: **LEVEL ONE** · Modelis: **FVM-1101** · EAN: **4015867195529** · Prekės kodas: **719542**



## 178,90 €

Kaina su PVM

Be PVM: **147,85 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Wired
- ✓ 100 Mbit/s 2000 m 1310 nm
- ✓ 10BASE-T, 100BASE-FX, 100BASE-TX
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Fiber ports quantity: 1 LC, SC, ST
- ✓ Black



## Aprašymas

FVM-1101 is remote Managed Fast Ethernet fiber media converter with OAM functions developed by our company. It can convert Ethernet signal between 10/100Base-Tx and 100Base-FX, It supports both half-duplex and full-duplex operations and a variety of fiber options. It is double fiber, multi mode, 2km media converter

Remote devices can be managed by fiber-connected OAM media converter or OAM switch when deployed as a stand-alone solution. It incorporates an easy to use Web user interface for operation, administration and maintenance, both locally and remotely. By offering IEEE802.3ah OAM compliance, this converter can be linked to any IEEE802.3ah compliant fiber switch and support loop back and dying gasp functions. All functions of this converter and the remotely connected converter can be configured and monitored via Web management, including bandwidth control, duplex, speed and VLAN configuration.

## Key Features

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už Psl. 1 galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) · [info@shopro.lt](mailto:info@shopro.lt) · +370 693 39903

- Built-in LFP (Link Fault Pass-through) (LLCF/LLR) Technology
- Web-based and SNMP Management
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Supports VLAN (tag-based, Q-in-Q)

## Techninė specifikacija

| Specifications                     |                                                    |
|------------------------------------|----------------------------------------------------|
| Sandėlio grupė                     | I/O Cards & Adapters [+365][-122]                  |
| Network                            |                                                    |
| Maximum data transfer rate         | 100 Mbit/s                                         |
| Converter input interface          | 10Base-T, 100Base-TX                               |
| Converter output interface         | 100Base-FX                                         |
| Networking standards               | IEEE 802.3, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x |
| Ethernet interface type            | Fast Ethernet                                      |
| Ethernet LAN data rates            | 10,100 Mbit/s                                      |
| Copper ethernet cabling technology | 10BASE-T, 100BASE-FX, 100BASE-TX                   |
| Jumbo frames support               | Yes                                                |
| Jumbo frames                       | 9000                                               |
| Flow control support               | Yes                                                |
| VLAN support                       | Yes                                                |
| Store-and-forward                  | Yes                                                |
| Duplex system                      | Full, Half                                         |
| Performance                        |                                                    |
| Maximum transfer distance          | 2000 m                                             |
| Wavelength                         | 1310 nm                                            |
| Features                           |                                                    |
| Web-based management               | Yes                                                |
| LED indicators                     | Activity, FDX, Link, Power                         |
| Product colour                     | Black                                              |
| Ports & interfaces                 |                                                    |
| Fiber optic connector              | LC, SC, ST                                         |
| Connectivity technology            | Wired                                              |
| Ethernet LAN (RJ-45) ports         | 1                                                  |
| Fiber ports quantity               | 1                                                  |
| Power                              |                                                    |

|                                   |             |
|-----------------------------------|-------------|
| Input voltage                     | 100 - 240 V |
| Output voltage                    | 5 V         |
| Output current                    | 2 A         |
| Weight & dimensions               |             |
| Width                             | 127 mm      |
| Depth                             | 156 mm      |
| Height                            | 32 mm       |
| Weight                            | 720 g       |
| Operational conditions            |             |
| Operating temperature (T-T)       | -10 - 55 °C |
| Operating relative humidity (H-H) | 5 - 90%     |
| Packaging data                    |             |
| Package width                     | 185 mm      |
| Package depth                     | 275 mm      |
| Package height                    | 62 mm       |
| Package weight                    | 880 g       |
| Package type                      | Box         |
| Certificates                      |             |
| Compliance certificates           | RoHS        |
| Certification                     | FCC, CE     |
| Logistics data                    |             |
| Country of origin                 | China       |
| Harmonized System (HS) code       | 85176990    |
| Master (outer) case width         | 360 mm      |
| Master (outer) case length        | 480 mm      |
| Master (outer) case height        | 390 mm      |
| Master (outer) case gross weight  | 17.5 kg     |
| Products per master (outer) case  | 17 pc(s)    |