

LevelOne RJ45 to SC Managed Gigabit Media Converter, Single-Mode Fiber, 20km

Gamintojas: **LEVEL ONE** · Modelis: **GVM-1220** · EAN: **4015867195406** · Prekės kodas: **719544**



219,91 €

Kaina su PVM

Be PVM: **181,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1000 Mbit/s 20000 m 1310 nm
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ 1000BASE-X
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Single-mode Fiber ports quantity: 1 FC, SC, ST
- ✓ Black



Aprašymas

GVM-1220 series is remote Managed Gigabit Ethernet fiber media converter with OAM functions developed by our company. It can convert Ethernet signal between 10/100/1000Base-T and 1000Base-X, It supports both half-duplex and full-duplex operations and a variety of fiber options. It is double fiber, single mode, 20km media converter

Remote devices can be managed by fiber-connected OAM media converter or OAM switch when deployed as a stand-alone solution. It incorporates an easy to use Web user interface for operation, administration and maintenance, both locally and remotely. By offering IEEE802.3ah OAM compliance, this converter can be linked to any IEEE802.3ah compliant fiber switch and support loop back and dying gasp functions. All functions of this converter and the remotely connected converter can be configured and monitored via Web management, including bandwidth control, duplex, speed and VLAN configuration.

Techninė specifikacija

Specifications	
Sandėlio grupė	I/O Cards & Adapters [+365][-122]
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Fiber ethernet cabling technology	1000BASE-X
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
VLAN support	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Performance	
Maximum transfer distance	20000 m
Wavelength	1310 nm
Fiber mode structure	Single-mode
Mean time between failures (MTBF)	30000 h
Features	
Internal	No
Web-based management	Yes
LED indicators	Activity, FDX, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	FC, SC, ST
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	100 - 240 V
Output voltage	5 V

Output current	2 A
----------------	-----

Weight & dimensions

Width	127 mm
-------	--------

Depth	156 mm
-------	--------

Height	32 mm
--------	-------

Weight	720 g
--------	-------

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
-----------------------------	-------------

Operating relative humidity (H-H)	5 - 90%
-----------------------------------	---------

Packaging data

Package width	185 mm
---------------	--------

Package depth	275 mm
---------------	--------

Package height	62 mm
----------------	-------

Package weight	880 g
----------------	-------

Package type	Box
--------------	-----

Certificates

Compliance certificates	RoHS
-------------------------	------

Certification	CE, FCC
---------------	---------

Logistics data

Country of origin	China
-------------------	-------

Harmonized System (HS) code	85176990
-----------------------------	----------

Master (outer) case width	360 mm
---------------------------	--------

Master (outer) case length	480 mm
----------------------------	--------

Master (outer) case height	390 mm
----------------------------	--------

Master (outer) case gross weight	17.5 kg
----------------------------------	---------

Products per master (outer) case	17 pc(s)
----------------------------------	----------