

LevelOne RJ45 to SC Fast Ethernet Media Converter, Single-Mode Fiber, 1310nm, 40km

Gamintojas: **LEVEL ONE** · Modelis: **FVT-1103** · EAN: **4015867208052** · Prekės kodas: **719596**



47,90 €

Kaina su PVM

Be PVM: **39,59 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports the transmission of extra-long packets up to 1.6KB
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ Single-mode fiber with SC connector for transmission of up to 40km
- ✓ Supports low-time lag transmission



Aprašymas

The LevelOne FVT-1103 single-mode fiber optic media converter with SC connector is perfectly suited to convert network signals between copper and fiber optic based networks. The converter has a 10/100Base-TX RJ-45 port, supports full-duplex and half-duplex connectivity as well as 10Base-T and 100Base-TX auto-sensing. A range of up to 40 km can be achieved with the appropriate single-mode fiber optic cables.

The converter can be used either stand-alone or as a plug-in module for the CHV-2000 19" chassis, which can accommodate up to 14 units for use in a central wiring closet.

Techninė specifikacija

Specifications

Sandėlio grupė

I/O Cards & Adapters [+365][122]

Network

Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Fiber ethernet cabling technology	100BASE-FX
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes

Performance

Maximum transfer distance	40000 m
Wavelength	1310 nm
Fiber mode structure	Single-mode
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm
Mean time between failures (MTBF)	100000 h

Features

Internal	No
LED indicators	Yes
Product colour	Black

Ports & interfaces

Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes

Power

Input voltage	5 V
Input current	1 A

Weight & dimensions

Width	94 mm
-------	-------

Depth	71 mm
Height	26 mm
Weight	200 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	230 mm
Package depth	150 mm
Package height	58 mm
Package weight	300 g
Package type	Box
Certificates	
Compliance certificates	RoHS
Certification	FCC, CE
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Master (outer) case width	440 mm
Master (outer) case length	420 mm
Master (outer) case height	305 mm
Master (outer) case gross weight	32 kg
Products per master (outer) case	40 pc(s)