

LevelOne Gigabit USB-C Network Adapter with USB Hub

 Gamintojas: **LEVEL ONE** · Modelis: **USB-0504** · EAN: **4015867226681** · Prekės kodas: **719753**


30,90 €

Kaina su PVM

 Be PVM: **25,54 €**


Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10/100/1000Mbps wire speed transmission and reception
- ✓ USB 3.0 SuperSpeed (5Gb/s)
- ✓ Add 3 x USB 3.0 ports to your USB Type-C devices
- ✓ Multi-platform support: Windows, Mac OS
- ✓ Built-in Wake-on-LAN feature to startup computers remotely
- ✓ Simple Plug and Play installation, no additional power supply required



Aprašymas

The LevelOne USB-C Hub and Gigabit Ethernet Combo Adapter allows you to connect to the internet easily through the built-in USB-C port on your laptop. This is an ideal solution for MacBook or other Windows computers that may have wireless built-in but don't come with an Ethernet port. Sometimes you need to physically connect to a network cable to help transfer files or access secure information. The USB-0504 easily does the job, all through your USB-C port. The USB-0504 also combines a regular USB hub. So you can connect external USB peripherals, such as a digital camera, printer or pen drive. The USB-0504 establishes a direct point-to-point contact between the hub and the adapter that plugged into your PC.

The USB-0504 is USB 1.0, 2.0, and 3.0 compliant. It also follows the Ethernet standards set by the IEEE 802.3/3u and 802.3ab, allowing you to take advantage of Gigabit Ethernet speeds of up to 1000Mbps. This provides a strong backbone for any high-speed broadband connection to the internet as well as fast speeds for the Local Area Network file transfers.

This makes the USB-0504 the best choice for reliability, efficiency and standard compliance.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+541][-77]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB Type-C
Interface	Ethernet
Ethernet LAN (RJ-45) ports	1
USB ports quantity	3
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Wake-on-LAN ready	Yes
Full duplex	Yes
Design	
Internal	No
Component for	PC/Laptop
Product colour	Silver
Chipset	Realtek RTL8153
Plug and Play	Yes
Country of origin	China
Power	
USB powered	Yes
System requirements	

Windows operating systems supported

Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

Mac operating systems supported

Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-5 - 80 °C
Operating relative humidity (H-H)	0 - 85%
Storage relative humidity (H-H)	0 - 85%

Weight & dimensions

Width	110 mm
Depth	23.5 mm
Height	16.5 mm
Weight	44 g

Packaging data

Package width	71 mm
Package depth	20 mm
Package height	152 mm
Package weight	64 g

Packaging content

Quick installation guide	Yes
--------------------------	-----

Technical details

Compliance certificates	CE, RoHS
-------------------------	----------