

Conceptronic DONN11G 6-in-1 USB 3.2 Gen 1 Docking Station, HDMI, 100W USB PD, USB 3.0, USB 2.0, SD, TF/MicroSD

Gamintojas: **CONCEPTRONIC** · Modelis: **DONN11G** · EAN: **4015867230879** · Prekės kodas: **719852**



36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6-in-1 USB-C to HDMI/USB-C PD/USB 3.0/USB 2.0/SD/TF multiport adapter
- ✓ Supports HDMI resolution up to 4K*2K 30Hz
- ✓ Supports USB Power Delivery (PD) up to 100W
- ✓ Data transfer speed up to 5Gb/s
- ✓ Simple Plug and Play installation
- ✓ Aluminum casing for heat dissipation
- ✓ Multi-platform support: Windows, Mac OS, Chrome OS



Aprašymas

This 6-in-1 USB 3.2 Gen 1 Docking Station makes it possible to expand your device's USB Type-C capacity with HDMI/USB-C PD/USB 3.0/USB 2.0 ports and card readers (SD, MicroSD/TF).

The docking station provides an easy way to add HDTV, or equipment such as a monitor or projector to any USB-C device such as a smartphone, portable gaming console, MacBook, Chromebook Pixel or any similar late-model laptop with USB-C ports. Perfect for home entertainment, office presentations and classroom teaching.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook Docks [+118][-14]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
HDMI ports quantity	1
Microphone in	No
Headphone outputs	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
HDMI version	1.4
Network	
Ethernet LAN	No
Performance	
Product colour	Grey
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), SD
Data transfer rate	5 Gbit/s
HD type	4K Ultra HD
Maximum digital resolution	4096 x 2160 pixels
Maximum refresh rate	30 Hz
Plug and Play	Yes
Housing material	Aluminium
Power	
Power source type	USB
USB cable length	0.12 m
Software	

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Mobile operating systems supported	Android 10.0, Android 11.0, Android 12.0, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 8.1, Android 9.0
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Weight & dimensions	
Width	30.2 mm
Depth	107.6 mm
Height	10.7 mm
Weight	55 g
Packaging data	
Package width	74 mm
Package depth	149 mm
Package height	21 mm
Package weight	75 g
Packaging content	
Quick start guide	Yes
Logistics data	
Master (outer) case width	230 mm
Master (outer) case length	400 mm
Master (outer) case height	205 mm
Master (outer) case gross weight	8 kg
Products per shipping (inner) case	100 pc(s)