

Conceptronic OZUL04BE 67W GaN USB PD Charger, Built-in USB-C Cable

Gamintojas: CONCEPTRONIC · Modelis: OZUL04BE · EAN: 4015867235591 · Prekės kodas: 719935



39,91 €

Kaina su PVM

Be PVM: 32,98 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High-Power GaN Technology: This charger utilizes advanced Gallium Nitride (GaN) technology, providing up to 67W of total power for faster and more efficient charging.
- ✓ Wide Compatibility: Supports a range of output options from 3.3V to 21.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ Enhanced Safety Features: Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ Efficiency and Fast Charging Technology: Incorporates USB Power Delivery (PD) 3.0 for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize charging efficiency and minimize heat generation.
- ✓ Included USB Cable: Features a built-in 1.8m USB-C cable for convenience and versatility.



Aprašymas

This charger features advanced Gallium Nitride (GaN) technology, delivering up to 67W of total power for faster and more efficient charging. It supports a broad range of output options from 3.3V to 21.0V across its ports, ensuring compatibility with a variety of devices from smartphones to laptops. Enhanced safety features include built-in protections against overload, short circuiting, and overheating, safeguarding both the charger and connected devices. The charger incorporates USB Power Delivery (PD) 3.0 for rapid charging and Programmable Power Supply (PPS) compliance to

optimize charging efficiency and reduce heat generation. Additionally, it includes a built-in 1.8m USB-C cable for added convenience and versatility.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook Chargers [+263][-61]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	1
Programmable power supply (PPS)	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	67 W
Power protection features	Overheating, Overload, Short circuit
Design	
Product colour	Black
Cable length	1.8 m
Plug and Play	Yes
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Input current	1.6 A
Maximum output voltage	21 V
Minimum output voltage	3.3 V
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	3 A
Output current (15V)	3 A
Output current (20V)	3.25 A
Power plug type	Type C
Weight & dimensions	
Width	50 mm

Depth	29 mm
Height	40 mm
Weight	158 g
Packaging data	
Package width	153 mm
Package depth	136 mm
Package height	36 mm
Package weight	36 g
Package type	Box
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Packaging content	
Quantity per pack	1 pc(s)
AC adapter included	Yes
Certificates	
Compliance certificates	CE, RoHS
Sustainability	
Sustainability certificates	ErP
Sustainability compliance	Yes
Logistics data	
Pallet net height	135.2 cm
Pallet net length	80 cm
Pallet net width	120 cm
Harmonized System (HS) code	8504408390
Pallet gross width	120 cm
Pallet gross length	80 cm
Pallet gross height	135.2 cm
Master (outer) case width	325 mm
Master (outer) case length	405 mm
Master (outer) case height	288 mm
Master (outer) case gross weight	9 kg

Products per master (outer) case	40 pc(s)
----------------------------------	----------

Country of origin	China
-------------------	-------

Other features

Gross weight of outer carton	9 kg
------------------------------	------

Outer carton dimensions (W x D x H)	325 x 405 x 288 mm
-------------------------------------	--------------------