

Conceptronic 1-Port 20W USB-C PD Charger

Gamintojas: CONCEPTRONIC · Modelis: ALTHEA14W · EAN: 4015867236451 · Prekės kodas: 719951



11,89 €

Kaina su PVM

Be PVM: 9,83 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dedicated Port Connector: Equipped with a USB-C ports (with PD 3.0), providing up to 20W of total power and high-speed charging for a wide range of devices with varying power requirement.
- ✓ Enhanced Safety Features: Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ Wide Compatibility: Supports a range of output options from 5.0V to 12.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ Efficiency and Fast Charging Technology: Incorporates USB Power Delivery (PD) 3.0 technology for efficient and rapid charging, ensuring broad device compatibility.



Aprašymas

This charger features a dedicated USB-C port with USB Power Delivery (PD) 3.0, delivering up to 20W of total power for high-speed charging across a variety of devices. It supports a wide range of output options from 5.0V to 12.0V, ensuring compatibility with both smartphones and laptops. The charger is designed with enhanced safety features, including protections against overload, short circuiting, and overheating, to keep both the charger and connected devices safe. With USB Power Delivery (PD) 3.0 technology, it provides efficient and rapid charging, making it a versatile solution for diverse charging needs.

Techninė specifikacija

Specifications

Sandėlio grupė	Notebook Chargers [+263][-61]
----------------	-------------------------------

Performance

Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	1
USB Type-C ports quantity	1
Fast charging	Yes
Fast charging technology	Power Delivery 3.0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3

Design

Product colour	White
----------------	-------

Power

Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	0.6 A
Maximum power	20 W
Maximum output voltage	12 V
Minimum output voltage	5 V
Output current (5V)	3 A
Output current (9V)	2.22 A
Output current (12V)	1.67 A

Weight & dimensions

Width	42 mm
Depth	78 mm
Height	41 mm
Weight	52 g

Packaging data

Package width	61 mm
Package depth	164 mm
Package height	33 mm
Package weight	33 g

Package type	Box
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	5 - 95%
Packaging content	
Manual	Yes
Certificates	
Compliance certificates	CE, REACH, RoHS
Sustainability	
Sustainability certificates	ErP
Sustainability compliance	Yes
Logistics data	
Harmonized System (HS) code	8504408390
Pallet gross width	120 cm
Pallet gross length	80 cm
Pallet gross height	180 cm
Master (outer) case width	450 mm
Master (outer) case length	450 mm
Master (outer) case height	380 mm
Master (outer) case gross weight	7 kg
Products per master (outer) case	100 pc(s)
Country of origin	China