

Lindy HDMI 2.0 EDID Emulator

Gamintojas: **LINDY** · Modelis: **32115** · EAN: **4002888321150** · Prekės kodas: **720154**



67,91 €

Kaina su PVM

Be PVM: **56,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Continuously emulates HDMI EDID information
- ✓ Supports resolutions up to 3840x2160@60Hz including HDCP 2.2 pass-through and HDR
- ✓ Uses cloned data or, when this is not available, stored pre-set screen resolutions/timings
- ✓ Powered via HDMI Source Interface
- ✓ 2 Year warranty



Aprašymas

The Lindy HDMI 2.0 EDID Emulator Adapter is designed for systems that require EDID signals to be continuously provided without interruption and helps overcome EDID related problems which can occur when using AV/KVM Extenders, Switches and Splitters. It can also be used in place of a monitor to keep the graphics card of a PC or Server awake for remote access via IP. With support for resolutions up to Ultra HD 4K 60Hz (via cloning) including High-Dynamic Range and with the ability to passthrough HDCP 2.2 content, the Emulator is suitable for use with the very latest PC and AV applications.

Some computer systems, KVM switches and digital video signage systems may interrupt the flow of EDID data, or may not be able to pass this information directly back to the video card's output port. This adapter can be used to quickly and easily clone the EDID data from a HDMI display so that the graphics card has direct access to the correct data from the display, the cloning process takes less than 10 seconds!

It is also possible to use the Emulator without cloning a display as it comes complete with preset EDID data for the most commonly used resolution/timing combinations, please see the Technical Information section for a full breakdown.

Techninė specifikacija

Specifications	
Sandėlio grupė	LFD Monitors [+22][-3]
Ports & interfaces	
Connector 1	HDMI
Connector 2	HDMI
Connector 1 gender	Male
Connector 2 gender	Female
Performance	
Product colour	Black
Supported video modes	720p
Data transfer rate	18 Gbit/s
Maximum resolution	3840 x 2160 pixels
Maximum refresh rate	75 Hz
Colour depth	24 bit
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-10 - 70 °C
Relative humidity	0 - 80%
Certificates	
Compliance certificates	RoHS
Certification	CE, FCC, REACH
Weight & dimensions	
Weight	8 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	136 mm
Package height	138 mm
Package weight	13 g

Package type

Polybag