

Lindy HDMI and IR over IP Extender - Receiver

Gamintojas: **LINDY** · Modelis: **38399** · EAN: **4002888383998** · Prekės kodas: **720377**



122,90 €

Kaina su PVM

Be PVM: **101,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Add additional HDMI over IP receivers to create larger networked distribution setups
- ✓ Supports IR extension from the transmitter
- ✓ Simple, scalable solution for developing 1-to-many installations
- ✓ 2 year warranty
- ✓ Supports resolutions up to 1920x1080@60Hz



Aprašymas

IP extenders provide reliable extension of HDMI signals on a network connection, allowing for point to point and mixed configurations when combined with network equipment such as switches. Utilising IP connectivity ensures a low cost, scalable extension solution that can be easily setup for a variety of small or larger scale scenarios.

The Lindy HDMI and IR over IP receiver is a supplementary solution for extending HDMI signals across greater distances via a local network setup and creating scalable IP installations by using multiple receivers when combined with 38398 and network equipment. As a point to point connection, the extender supports distances up to 150m using Cat.6 cable, or when combined with a network switch can be expanded for much larger distribution systems with up to 3 layers of network equipment. Adding receivers provides additional flexibility to the setup to distribute content into various locations or displays at distance, great for use in retail, connected office installations or educational setups.

Supporting resolutions up to Full HD 1920x1080@60Hz 4:4:4 8bit, this extender provides high quality content, good for eye catching digital signage,

residential installations or AV distribution in hospitality. IR extension also provide simple control via an included IR emitter and receiver cable using an IR remote.

Please Note: Use a dedicated network specially for larger installations. The HDMI over IP Extender distributes in full 1080p resolution using H.265 video compression.

Techninė specifikacija

Specifications	
Sandėlio grupė	LFD Monitors [+22][-3]
Features	
Type	AV receiver
Maximum resolution	1920 x 1080 pixels
Cable types supported	Cat5e, Cat6
Maximum transfer distance	150 m
Chipset	SSD203D
Maximum refresh rate	60 Hz
Audio output channels	2.0 channels
Supported network protocols	IP
Infrared (IR) frequency range	20 - 60 kHz
Bandwidth	6.75 Gbit/s
Video compression formats	H.265
HDCP	Yes
HDCP version	1.4
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes
RJ-45 input ports	1
Number of HDMI outputs	1
HDMI version	1.3
Remote (IR) input	1
DC-in jack	Yes
Power	
Power source type	DC
Operating voltage	5 V
Output current	1 A

Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width	88 mm
Depth	16.5 mm
Height	61.2 mm
Weight	236 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	146 mm
Package depth	65 mm
Package height	105 mm
Package weight	357 g
Package type	Box
Packaging content	
AC adapter included	Yes
Cables included	IR
Included power plug types	AU, EU, UK, US
Manual	Yes
Technical details	
Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS
Sustainability compliance	Yes