

Lindy HDMI 4K30 Audio Extractor

Gamintojas: **LINDY** · Modelis: **38167** · EAN: **4002888381673** · Prekės kodas: **720468**



86,90 €

Kaina su PVM

Be PVM: **71,82 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extract stereo or multi-channel audio from a HDMI signal
- ✓ Support resolutions up 4096x2160@30Hz 4:4:4 8bit
- ✓ Supports various audio formats including LPCM, Dolby Digital 2/5.1 and DTS-HD
- ✓ CEC Pass-through
- ✓ 2 year warranty



Aprašymas

The Lindy HDMI 4K Audio Extractor is an effective solution for extracting audio from a HDMI source to both digital and analogue audio devices, while sending the video signal to a 4K display or projector. This is a perfect solution for connecting Non-HDMI AV receivers, or analogue 2-channel speaker setups to an HDMI source device, while also ideal for extracting audio and video to a display that requires separate speakers such as a PC monitor.

The extractor supports high quality 4096x2160@30Hz resolutions with additional pass-through support for CEC, to allow source devices to be controlled from a TV control, and HDCP 1.4, this is ideal for use with source devices such as set top boxes, games consoles and Blu-Ray Players.

This audio extractor allows output to both digital formats via Optical and HDMI and analogue via L/R connections, ensuring seamless compatibility with an amplifier, sound bar or 2-channel speaker setup. With support for multi-channel audio including DTS: HD and Dolby Digital 5.1, this device will ensure an impressive three-dimensional surround sound performance to compliment films, games and music when connected to an audio device. The 3.5mm analogue connection ensures 2-channel speaker set ups can also be connected to the extractor.

Featuring a neat switch to fully control which source audio EDID is used and the ability to be powered via USB from the source or display device, the extractor provides simple use and installation, great for both AV installations in the home or in commercial settings. With a minimalist and stylish design, it can also be hidden out of sight to compliment the popular trend of discreet AV installations.

Techninė specifikacija

Specifications	
Sandėlio grupė	LFD Monitors [+22][-3]
Inputs	
Digital audio coaxial in	0
Digital audio optical in	0
HDMI in	1
DC-in jack	Yes
USB 1.1 ports quantity	0
Outputs	
Audio (L/R) out	1
Digital audio coaxial out	1
Digital audio optical out	1
S/PDIF out port	Yes
Number of HDMI outputs	1
Technical details	
Maximum data transfer rate	10200 Mbit/s
HDCP	Yes
HDCP version	1.4
Chipset	EP91A2E
HDMI version	1.4
HDMI pass-through	Yes
CEC pass-through	Yes
Input impedance	100 Ω
Output impedance	100 Ω
Supported sample rates	192 kHz
Supported chroma subsampling	4:4:4
Audio codecs	Dolby Digital 2/5.1, DTS-HD
Accuracy	0.1 dB
Product colour	Black
Maximum resolution	4096 x 2160 pixels

Audio recording formats	LPCM
Housing material	Metal
Compliance certificates	REACH, RoHS
Certification	CE, UKCA, FCC, RoHS, REACH
Power	
Power consumption (typical)	5 W
Power note	5.5/2.1mm DC
Weight & dimensions	
Width	65 mm
Depth	88 mm
Height	24 mm
Weight	118 g
Operational conditions	
Operating temperature (T-T)	-15 - 55 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Packaging data	
Quantity	1
Cables included	DC to USB Type-A
Manual	Yes
Package width	202 mm
Package depth	144 mm
Package height	55 mm
Package weight	250 g
Package type	Box
Logistics data	
Harmonized System (HS) code	85176990