

LINDY USB 3.0 Gigabit Ethernet Converter aktiv

Gamintojas: **LINDY** · Modelis: **43298** · EAN: **4002888432986** · Prekės kodas: **720556**



30,90 €

Kaina su PVM

Be PVM: **25,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects a USB 3.0 Type A computer to a Gigabit Ethernet network
- ✓ Supports 10/100/1000BASE-T, full and half duplex mode
- ✓ USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- ✓ Bus-powered with no external power supply required
- ✓ 2 year warranty



Aprašymas

The Lindy USB 3.0 Gigabit Ethernet Converter allows users to conveniently connect a notebook or ultrabook to a Gigabit Ethernet network via a Type A USB port.

This converter is ideal for ultrabooks or notebooks which do not feature wired network connectivity and for locations which lack wireless connectivity or where it is unreliable or slow.

With its small size and lightweight design this USB 3.0 Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host

interface.USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+541][-77]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB
Interface	Ethernet
Ethernet LAN (RJ-45) ports	1
USB connector form factor	Straight
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	5000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Design	
Internal	No
Component for	PC/Laptop
Product colour	Silver
Chipset	Realtek RTL8153
Certification	CE, UKCA, FCC, RoHS, REACH, California Proposition 65
Compatible products	USB Type A equipped computers
Power	
USB powered	Yes
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	24 mm

Depth	58 mm
Height	16 mm
Weight	27 g
Packaging data	
Package type	Polybag
Package width	194 mm
Package depth	174 mm
Package weight	30 g
Other features	
Housing material	Aluminium
Cable length	0.135 m