

Lindy 4 Port USB 3.0 Hub

Gamintojas: **LINDY** · Modelis: **43324** · EAN: **4002888433242** · Prekės kodas: **720849**



18,90 €

Kaina su PVM

Be PVM: **15,62 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects 4 Type A USB peripherals to a Type A Port
- ✓ Supports SuperSpeed data rates of up to 5Gbps
- ✓ Handy and stylish design with integrated cable
- ✓ Compatible with all USB Type A equipped computers
- ✓ 2 year warranty



Aprašymas

The Lindy 4 Port USB 3.0 Hub provides 4 USB Type A SuperSpeed ports for connecting USB peripherals to a USB Type A equipped computer. Capable of data transfer speeds of up to 5Gbps, the hub is also backwards compatible with USB 2.0 and 1.1.

The hub is powered by the USB Bus, while it's functional, stylish design with integrated cable make it the perfect companion for mobile devices. With 'Plug and Play' installation, no drivers are required, therefore this hub can be installed with minimum difficulty, ideal for both professional and first time users.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+541][77]
Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
Hub interfaces	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
Housing material	Aluminium, Plastic
Cable length	0.3 m
Power	
Power supply type	USB
Weight & dimensions	
Width	103 mm
Depth	26 mm
Height	18 mm
Weight	60 g
Packaging data	
Package width	174 mm
Package depth	20 mm
Package height	194 mm
Package weight	70 g
Operational conditions	
Operating temperature (T-T)	10 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Logistics data	
Harmonized System (HS) code	84719000

Technical details

Compliance certificates REACH, RoHS

Matmenys ir svoris

Matmenys (l × p × a) 14,00cm × 14,00cm × 2,00cm