

AG Neovo TX-10 25.6 cm (10.1") 1280 x 800 pixels LED

Gamintojas: **AG NEOVO** · Modelis: **TX100011E0100** · EAN: **4710739596274** · Prekės kodas: **720979**



481,89 €

Kaina su PVM

Be PVM: **398,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Incorporates projected capacitive touch technology
- ✓ 10-point simultaneous multi-touch capability
- ✓ Flush touch screen makes surface neat
- ✓ Plastic resin bezel ensures an airtight fit
- ✓ Front-sided IP65 rating compliant to protect the screen from liquid and dust
- ✓ Glass used in the touchscreen has passed the UL60950 ball-drop test for high-impact resistance and durability
- ✓ Support high operating temperature of up to 50°C (122°F)
- ✓ Wired (up to 1.53 meters) OSD controller is ideal for remote OSD control
- ✓ VESA standard mounting interface and included side mounting brackets for flexible installation
- ✓ Flexible display orientation: Landscape/Portrait



Aprašymas

The TX-10 Multi-touch Interactive Display, with its 10.1-inch, 10-point touch screen, brings the experience of a tablet into the form factor of a monitor. Its foam seal design supports seamless integration into kiosks and its front-side IP65 rating protects the screen from dust and water. External mounting brackets are provided for installation in a wide variety of application environments—in a meeting room as a scheduling display, or in a number of public, commercial, and industrial interactive applications. Allowing for either landscape or portrait orientation, the TX-10 multi-touch interactive display is the perfect fit.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitors [+653][-245]
Display	
Display diagonal	25.6 cm (10.1")
Display resolution	1280 x 800 pixels
Display technology	LED
Pixel pitch	0.169 x 0.169 mm
Maximum refresh rate	60 Hz
Response time	5 ms
Contrast ratio (typical)	1300:1
Touchscreen	Yes
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Design	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
LED indicators	Yes
Certification	CE, LVD, BSMI, RoHS, REACH, WEEE
Performance	
Windows operating systems supported	Windows 10, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Audio	
Built-in speaker(s)	No
Built-in microphone	No
Camera	
Built-in camera	No
Ports & interfaces	
HDMI ports quantity	1
HDMI version	1.3a
DisplayPorts quantity	1
VGA (D-Sub) ports quantity	1
Packaging data	

Package width	370 mm
Package depth	160 mm
Package height	325 mm
Package weight	2.4 kg
Packaging content	
Cables included	AC, DisplayPort, USB, VGA
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Technical details	
Compliance certificates	CE, REACH, RoHS, WEEE
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	37,00cm × 33,00cm × 16,00cm