

Lindy USB 3.0 to 2.5G Ethernet Converter

Gamintojas: **LINDY** · Modelis: **43313** · EAN: **4002888433136** · Prekės kodas: **721196**



41,90 €

Kaina su PVM

Be PVM: **34,63 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects a USB 3.0 computer to a 2.5 Gigabit Ethernet network
- ✓ Supports up to 2.5G Ethernet bandwidth*
- ✓ USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- ✓ Bus-powered with no external power supply required
- ✓ 2 year warranty



Aprašymas

USB to Ethernet Converters allow users to connect USB equipped devices to a Gigabit Ethernet network.

The Lindy USB 3.0 Type A to 2.5G Ethernet Converter allows users to conveniently connect a computer or notebook to a Gigabit Ethernet network via a Type A USB port. It supports extremely high data rates up to 2.5Gbps* on existing Cat.5e/6 cabling infrastructure.

This converter is ideal for thin and light ultrabooks or tablets which do not feature wired network connectivity. With its small size and lightweight design this USB 3.0 to 2.5G Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

* please make sure that the connected switch supports 2.5GBASE-T (IEEE 802.3bz)

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	I/O Cards & Adapters [+365][-122]
Ports & interfaces	
Connector 1	USB-A
Connector 2	RJ-45
Connector 1 gender	Male
Connector 2 gender	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Cable length	0.27 m
Performance	
Product colour	Silver
Housing material	Aluminium
Chipset	RTL8156B
Compatible operating systems	Windows, Mac, Linux OS
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-20 - 70 °C
Relative humidity	5 - 95%
Certificates	
Compliance certificates	REACH, RoHS
Certification	CE, FCC, POP, CP65
Weight & dimensions	
Width	60 mm
Depth	22 mm
Height	17 mm
Weight	36 g

Packaging content

Manual	Yes
--------	-----

Packaging data

Package weight	40 g
----------------	------