

LevelOne RJ45 to SFP Gigabit Media Converter, PoE PSE

Gamintojas: **LEVEL ONE** · Modelis: **GVT-2012** · EAN: **4015867227657** · Prekės kodas: **721326**



98,91 €

Kaina su PVM

Be PVM: **81,74 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Transfers data from 10/100/1000Base-T copper to fiber interfaces
- ✓ IEEE 802.3af/at PoE PSE with 30W power budget
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ IEEE 802.3z Gigabit Ethernet compliant



Aprašymas

The GVT-2012 is a Single-Port, End-Span IEEE 802.3at High Power over Ethernet converter designed specifically to satisfy the growing demand for higher power required network equipment such as PTZ (Pan, Tilt & Zoom) network cameras, PTZ speed dome, color touch-screen VoIP telephones, multi-channel (IEEE 802.11a / b / g / n) wireless LAN access points and other network devices that need higher power to function normally. The GVT-2012 is High Power over Ethernet converter series is an ideal solution to delivering data and power to network devices directly via the RJ45 Port interface without the need for installing extra power outlets and electrical cabling.

Techninė specifikacija

Specifications

Sandėlio grupė	I/O Cards & Adapters [+365][-122]
Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100Base-T, 1000Base-T
Converter output interface	1000Base-X
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Performance	
Mean time between failures (MTBF)	400000 h
Features	
Internal	No
LED indicators	Link, Power
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	2 A
Power consumption (max)	33 W
Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	30 W

External power adapter	Yes
Weight & dimensions	
Width	94 mm
Depth	71 mm
Height	26 mm
Weight	182 g
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	202 mm
Package depth	145 mm
Package height	72 mm
Package weight	850 g
Package type	Box
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA
Logistics data	
Country of origin	China
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet gross height	170.4 cm
Harmonized System (HS) code	8517620000
Master (outer) case width	425 mm
Master (outer) case length	310 mm
Master (outer) case height	390 mm
Master (outer) case gross weight	17.7 kg
Products per master (outer) case	20 pc(s)