

# LogiLink UA0360 video cable adapter 0.15 m USB Type-C Mini DisplayPort White

Gamintojas: **LOGILINK** · Modelis: **UA0360** · EAN: **4052792057553** · Prekės kodas: **721464**



## 17,90 €

Kaina su PVM

Be PVM: **14,79 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Comply with USB-C specification
- ✓ Connected devices must support USB DP/HDMI Alternate Mode
- ✓ 2x shielded
- ✓ Plastic housing
- ✓ Nickel plated



## Aprašymas

### Product information "USB 3.2 Gen 1x1, USB-C to Mini DisplayPort adapter, 4K/60 Hz" from LogiLink

Experience 4K video playback through USB-C on an extended display. LogiLink's UA0360 allows the user to connect a computer with USB-C port (like your MacBook or Chromebook) to a monitor or TV with Mini DisplayPort interface. The connected display can act as a mirror or extended desktop of the main display on your computer. In this way you can experience 4K at 60 Hz video playback through the Mini DisplayPort interface and USB-C for both work and entertainment. Even without needing an additional power supply for the adapter.

Input: 1x USB-C male

Output: 1x Mini DisplayPort female

Video output resolution: Up to 4K (60 Hz)

Compliant with USB 3.2 Gen1x1 specifications

With USB Type-C reversible plug

Designed to be used with DisplaPort Alternate Mode (DP Alt Mode) devices, such as the MacBook, Chromebook and other USB-C devices.

Cable length: 0.15m

## Techninė specifikacija

| Specifications                    |                                   |
|-----------------------------------|-----------------------------------|
| Sandėlio grupė                    | I/O Cards & Adapters [+365][-122] |
| Features                          |                                   |
| Cable length                      | 0.15 m                            |
| Connector 1                       | USB Type-C                        |
| Connector 2                       | Mini DisplayPort                  |
| Connector 1 gender                | Male                              |
| Connector 2 gender                | Female                            |
| Connector 1 form factor           | Straight                          |
| Connector 2 form factor           | Straight                          |
| Maximum resolution                | 3840 x 2160 pixels                |
| Supported graphics resolutions    | 3840 x 2160                       |
| Maximum refresh rate              | 60 Hz                             |
| Product colour                    | White                             |
| Operational conditions            |                                   |
| Operating temperature (T-T)       | 0 - 45 °C                         |
| Storage temperature (T-T)         | -10 - 70 °C                       |
| Operating relative humidity (H-H) | 10 - 85%                          |
| Storage relative humidity (H-H)   | 5 - 90%                           |
| Packaging content                 |                                   |
| Manual                            | Yes                               |
| Logistics data                    |                                   |
| Harmonized System (HS) code       | 84733080                          |