

Lindy HDMI 4K60 to DisplayPort 1.2 Converter

Gamintojas: **LINDY** · Modelis: **38327** · EAN: **4002888383271** · Prekės kodas: **721689**



48,90 €

Kaina su PVM

Be PVM: **40,41 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects an HDMI source to a DP display
- ✓ Supports resolutions up to 4K UHD 3840x2160@60Hz
- ✓ Enclosed USB cable for power supply
- ✓ High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- ✓ 2 year warranty

Aprašymas

A converter allows devices which use different interfaces e.g. HDMI and DVI to connect to one another by converting one signal to the other.

The Lindy HDMI 4K60 to DisplayPort 1.2 Converter allows the connection of HDMI source devices, such as a PC, Blu-ray player or media player to DisplayPort monitors digital signage and LFDs (Large Format Displays). Supporting resolutions up to 3840x2160@60Hz 4:4:4 8bit, this converter ensures superior clarity content within innovative workspaces, engaging collaboration environments and educational setups. Immersive multi-channel audio is supported up to 7.1CH to compliment the video on screen.

For added convenience the converter features a USB power cable, allowing the converter to be externally powered when used with low power HDMI sources. The converter can also be used to add an additional display to extend the available desktop workspace. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient plug and play installation.

Techninė specifikacija

Specifications

Sandėlio grupė

I/O Cards & Adapters [+365][-122]

Features

Cable length

157 m

Connector 1	HDMI Type A (Standard)
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Power source	USB
HDMI version	2
DisplayPort version	1.2
Maximum resolution	3840 x 2160 pixels
Data transfer rate	21.6 Gbit/s
Maximum refresh rate	60 Hz
Refresh rate at maximum resolution	60 Hz
Bend radius (min)	2.5 cm
Product colour	Black
Chipset	LT6711A
Jacket material	Nylon/Polyvinyl Chloride (PVC)
Cable type	Round cable
Connector housing material	Acrylonitrile butadiene styrene (ABS)
Colour depth	8 bit
Colour sampling	4:4:4
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 45 °C
Operating relative humidity (H-H)	20 - 70%
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Weight & dimensions	
Connector 1 dimensions (WxDxH)	30 x 8 x 17 mm
Connector 2 dimensions (WxDxH)	71 x 12 x 31 mm
Weight	50 g
Packaging data	
Package width	174 mm
Package depth	194 mm

Package height	20 mm
Package weight	60 g
Package type	Polybag
Packaging content	
Quantity per pack	1 pc(s)
Sustainability	
Sustainability compliance	Yes