

Lindy HDMI ARC Audio Extractor

Gamintojas: **LINDY** · Modelis: **38363** · EAN: **4002888383639** · Prekės kodas: **721967**



68,90 €

Kaina su PVM

Be PVM: **56,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ ARC Enabled: Extract audio signal from ARC (Audio Return Channel) enabled HDTV to analogue stereo output, for audio receiver/amplifier/headphones
- ✓ CEC Pass Through
- ✓ Support PCM 2.0, Dolby 5.1, DTS 5.1 audio downmix to 2 channel stereo audio output
- ✓ 2 Year Warranty



Aprašymas

The Lindy HDMI ARC Audio Extractor is an effective solution for extracting audio from a HDMI display to analogue audio devices.

The extractor supports high quality 4096x2160@30Hz resolutions with additional pass-through support for CEC, to allow source devices to be controlled from a TV control, and HDCP 1.4, this is ideal for use with source devices such as set top boxes, games consoles and Blu-Ray Players.

This audio extractor allows output to HDMI and analogue via L/R connections, ensuring seamless compatibility with an amplifier, sound bar or 2-channel speaker setup. With support for multi-channel audio including DTS: HD and Dolby Digital 5.1, this device will ensure an impressive three-dimensional surround sound performance to compliment films, games and music when connected to an audio device. The 3.5mm analogue connection ensures 2-channel speaker set ups can also be connected to the extractor, perfect for use with PC monitors which may require separate speakers.

Techninė specifikacija

Specifications	
Sandėlio grupė	LFD Monitors [+22][-3]
Inputs	
USB connector type	Micro-USB
HDMI in	1
Outputs	
Audio (L/R) out	1
Headphone out	Yes
Technical details	
Frequency range	20 - 20000 Hz
Chipset	SPHE8107S
HDMI version	1.4
CEC pass-through	Yes
Output impedance	100 Ω
Supported sample rates	192 kHz
Product colour	Silver
Housing material	Plastic
Warranty period	2 year(s)
Signal-to-Noise Ratio (SNR)	101 dB
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
Certification	California Proposition 65
Sustainability compliance	Yes
Power	
Power consumption	500 mA
Input voltage	5 V
Weight & dimensions	
Width	70 mm
Depth	65 mm
Height	27 mm
Weight	81 g
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Operating relative humidity (H-H)	20 - 90%
-----------------------------------	----------

Packaging data

Quantity	1
Cables included	USB Type-A to Micro-USB Type-B
Manual	Yes
Package width	146 mm
Package depth	105 mm
Package height	65 mm
Package weight	174 g
Package type	Box