

Lindy 4 Port USB 3.0 Metal Hub

Gamintojas: **LINDY** · Modelis: **43374** · EAN: **4002888433747** · Prekės kodas: **722121**



73,89 €

Kaina su PVM

Be PVM: **61,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Provides 4 USB 3.0 SuperSpeed ports with data rates up to 5Gbps
- ✓ Hard-wearing USB Hub - Perfect for industrial applications
- ✓ Robust metal housing with high EMC protection and integrated brackets for mounting
- ✓ USB bus-powered, or can be externally powered
- ✓ 2 year warranty



Aprašymas

The Lindy 4 Port USB 3.0 Metal Hub has been designed to provide reliable performance in demanding operational environments. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this Hub is the ideal solution for use in industrial environments.

Backwards compatibility with USB 2.0/1.1/1.0 means the hub can simultaneously support older USB peripherals or systems that lack USB 3.0 capabilities, extending their lifetime and giving a greater return on investment. The hub also supports MTT technology which guarantees highest possible throughput speed for USB 1.1 devices.

Each port features individual short circuit protection, while the included power supply ensures secure and uninterrupted electricity supply.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+541][-77]
Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-B
Hub interfaces	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
Housing material	Metal
LED indicators	Yes
Cable type	Round cable
Cable length	0.8 m
Certification	CE, UKCA, FCC, RoHS & REACH, California Proposition 65
Power	
Power supply type	DC
Weight & dimensions	
Width	125 mm
Depth	74.6 mm
Height	22 mm
Weight	256 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	260 mm
Package depth	180 mm
Package height	70 mm
Package weight	650 g

Package type	Box
--------------	-----

Packaging content

Manual	Yes
--------	-----

Operational conditions

Minimum operating temperature	0 °C
-------------------------------	------

Maximum operating temperature	50 °C
-------------------------------	-------

Operating temperature (T-T)	0 - 50 °C
-----------------------------	-----------

Operating temperature (T-T)	-20 - 60 °F
-----------------------------	-------------

Operating relative humidity (H-H)	0 - 90%
-----------------------------------	---------

Technical details

Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
-------------------------	--

Sustainability

Sustainability compliance	Yes
---------------------------	-----