

Lindy HDMI 8K60 to DisplayPort 1.4 Converter

Gamintojas: **LINDY** · Modelis: **38329** · EAN: **4002888383295** · Prekės kodas: **722190**



82,90 €

Kaina su PVM

Be PVM: **68,51 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects an HDMI source to a DP display
- ✓ Supports resolutions up to 4K UHD 3840x2160@120Hz or 8K and 7680x4320@60Hz
- ✓ Enclosed USB cable for power supply
- ✓ High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- ✓ 2 year warranty



Aprašymas

A converter allows devices which use different interfaces e.g. HDMI and DVI to connect to one another by converting one signal to the other.

The Lindy HDMI 8K60 to DisplayPort 1.4 Converter allows the connection of HDMI source devices, such as a PC, Blu-ray player or media player to DisplayPort monitors digital signage and LFDs (Large Format Displays). Supporting resolutions up to 8K 7680x4320@60Hz or 3840x2160@120Hz, this converter ensures superior clarity content within innovative workspaces, engaging collaboration environments and educational setups. Immersive multi-channel audio is supported up to 7.1CH to compliment the video on screen.

For added convenience the converter features a USB power cable, allowing the converter to be externally powered when used with low power HDMI sources. The converter can also be used to add an additional display to extend the available desktop workspace. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient plug and play installation.

Techninė specifikacija

Specifications	
Sandėlio grupė	I/O Cards & Adapters [+365][-122]
Features	
Cable length	0.157 m
Connector 1	HDMI Type A (Standard)
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Power source	USB
HDMI version	2.1
HDCP	Yes
HDCP version	2.3
DisplayPort version	1.4
Maximum resolution	7680 x 4320 pixels
Data transfer rate	48 Gbit/s
Maximum refresh rate	120 Hz
Refresh rate at maximum resolution	60 Hz
Bend radius (min)	2.5 cm
Product colour	Black
Chipset	LT6711GX_U2
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 45 °C
Operating relative humidity (H-H)	20 - 70%
Storage relative humidity (H-H)	20 - 70%
Weight & dimensions	
Cable diameter	4.8 mm
Weight	30 g
Packaging data	

Package type	Polybag
--------------	---------

Packaging content

Packaging content	USB Type A to Micro-B Cable
-------------------	-----------------------------

Logistics data

Warranty period	2 year(s)
-----------------	-----------