

TP-Link TL-WN8200ND network card WLAN 300 Mbit/s

Gamintojas: **TP-LINK** · Modelis: **TL-WN8200ND(UN)** · EAN: **6935364050740** · Prekės kodas: **722375**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wireless
- ✓ USB WLAN
- ✓ 300 Mbit/s
- ✓ Wi-Fi Single-band (2.4 GHz)



Aprašymas

What This Product Does

TP-LINK TL-WN8200ND is a 300Mbps high power wireless adapter that allows users to enable their PCs or notebooks with extremely powerful wireless capability to deliver performance enhancements. The adapter adopts high power design which offers up to 10 times the range of conventional adapters. One of the TL-WN8200ND's best features is its stronger penetrability, which can effectively ensure that signal still remains reliable when it passes through multiple walls or floors.

High Receive Sensitivity for Reliable Signal

TL-WN8200ND features its high receive sensitivity, which could let you move further away from the access point while still maintaining the same wireless signal. In this case, using TL-WN8200ND means that you don't have to move the laptop like a divining rod, and you can easily pick up the network with its strong sensitivity.

Two 5 dBi External Detachable Antennas

Two high gain external antennas insure stronger transmission and reception capacity. The two detachable antennas can be rotated and adjusted in different directions to fit various operation environments. For even more demanding applications, the antennas can also be replaced with diverse

indoor antennas or directional antennas (using standard RP-SMA connector) to show even greater flexibility and wider wireless coverage.

One Button for Security Setup

TL-WN8200ND supports Wi-Fi Protected Setup™ (WPS) that allows users to simply press the "WPS" button on the exterior, instantly establishing a highly secured connection. Not only is it faster than normal security setups but more convenient in that you don't need to remember any password!

Desktop-Style Design & 1.5m USB Extension Cable

Besides the fashionable and novelty exterior, the desktop-style design is beneficial for the signal reception in various application environments, guaranteeing the smooth and stable signal. And TL-WN8200ND also provides 1.5m USB extension cable, convenient for your installation, even for the desktop equipment.

Bundled CD for Easy Operation

TL-WN8200ND comes with a CD with utility that helps you complete the software installation and wireless network settings, including security configurations and wireless connection, which is convenient for users, even for novice users.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Sticks [+45][−37]
Ports & interfaces	
Connectivity technology	Wireless
Host interface	USB
Interface	WLAN
Network	
Maximum data transfer rate	300 Mbit/s
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi	Yes
Wi-Fi band	Single-band (2.4 GHz)
Frequency range	2.4 - 2.4835 GHz
Top Wi-Fi standard	Wi-Fi 4 (802.11n)
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
WLAN data transfer rates supported	150,300 Mbit/s
Security algorithms	128-bit WEP, 64-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS
Design	
Internal	No
Product colour	Black
Antenna	Yes
Antenna design	External
Antenna connector type	RP-SMA
Antenna direction type	Omni-directional

Antenna gain level (max)	5 dBi
Transmitting power (CE)	20 dBm
Transmitting power (FCC)	27 dBm
WPS push button	Yes
LED indicators	Yes
Operating modes	Infrastructure mode

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.9 Mavericks
Linux operating systems supported	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	90.8 mm
Depth	60.8 mm
Height	24.5 mm

Packaging data

Package width	200 mm
Package depth	150 mm
Package height	39 mm
Package weight	250 g

Packaging content

Cables included	USB
Resource CD	Yes
Quick installation guide	Yes
Technical details	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Logistics data	
Harmonized System (HS) code	85176990
Sustainability	
Sustainability compliance	Yes