

# ASUS Pro H610T D4-CSM Intel H610 LGA 1700 Thin Mini ITX

Gamintojas: **ASUS** · Modelis: **90MB1AM0-M0EAYC** · EAN: **4711081679851** · Prekės kodas: **723973**



## 147,90 €

Kaina su PVM

Be PVM: **122,23 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Intel LGA 1700 „Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, „Intel® Pentium®“
- ✓ PC Thin Mini ITX Intel H610 7.1 kanalai
- ✓ DDR4-SDRAM 2 SO-DIMM Maksimali vidinė atmintis: 64 GB
- ✓ HDD & SSD M.2, SATA III Palaikomų saugojimo tvarkyklių skaičius: 3
- ✓ BIOS tipas: UEFI AMI 128 Mbit
- ✓ Gigabitinis eternetas



## Aprašymas

## ASUS Corporate Stable Model

ASUS Corporate Stable Model (CSM) is a commercial program designed to provide stable and reliable motherboards. Offering up to 36-month product lifecycle support and 6-month end-of-life notice to allow sufficient lead times for your organization to get ready for product transitions. Each purchase of an ASUS CSM motherboard comes with ASUS Control Center Express - server-grade IT management software.

## ASUS Control Center Express

ASUS Control Center Express is a real-time IT monitoring and management tool designed for business that improves productivity and enhances security, helping prevent unauthorized access and data leaks. The intuitive dashboard enables easy, real-time hardware and software management across your organization. Purchase of a Pro motherboard entitles you to a copy of Control Center Express – a US\$60

## Optimize IT endpoint management

Designed to assist IT staff in monitoring and controlling devices within their corporate networks, and facilitate inventory checking in multiple locations remotely

## Automate IT maintenance

Allows IT staff to schedule automatic updates of the latest BIOS, software and utilities to specific or all devices at off-peak times, enhancing system stability and IT operational flexibility

## Securely manage all of endpoints

Securely manage endpoint configuration, portable storage access and PC software applications by enabling them to create grouping rules on individual devices

## ASUS Self-recovering BIOS

ASUS-exclusive BIOS protection technology automatically recovers the system BIOS with a verified backup in the event of an update failure, preventing the need to replace or reinstall hardware.

## Trusted Platform Module(TPM)

Hardware-based security offers better data protection, enhances network security, protects digital identities and ensures platform integrity.

## Certified NIST SP 800-147

ASUS Business motherboard is certified by the national computer security standards.

## ASUS Secure Boot

ASUS business motherboard is set to check the firmware and signature of each piece of boot software.

ASUS Self-recovering BIOS

With ASUS Self-recovering BIOS

The user simply needs to reboot the system and ASUS Self-recovering BIOS will restore the latest BIOS update.

Anti-moisture Coating

Protection against moisture and corrosion

An innovative moisture-resistant coating protects the motherboard in humid environments, such as factories, libraries, data centers and internet cafes. It also minimizes internal corrosion by preventing adhesion and migration of moisture, prolonging the life of the motherboard.

Overvoltage Protection

World-class circuit-protecting power design

An exclusive circuit design with built-in voltage regulators to protect your chipset, connectivity ports, and audio codecs from damage caused by

unexpected high-level voltages from unstable or inferior power supplies.

## 24/7 Reliability Test

Optimized for twenty-four seven operations, the motherboard is tested under temperature up to 45°C and relative humidity up to 80% to ensure it can handle diverse temperature and humidity range of different location.

## ASUS Commercial BIOS Kit

ASUS understands how important a customized product impacts users' mind share, experience the brand new Commercial BIOS Kit for partial BIOS update solution!

## Remote IT Management

The onboard SMBUS header\* connects to a DASH LAN card for remote IT management. DASH is a desktop and mobile architecture system hardware that allows the motherboard to be managed via the network.

## Q-LED Core

The Q-LED Core display produces light patterns by power LED during the Power-On Self-Test (POST) that can help users troubleshoot potential issues.

## ASUS COM Debug Header

This 6-1 pin COM debug header allows for faster and more efficient motherboard troubleshooting. IT administrators can view error and debugging codes to get a better idea of initialization and recovery processes when connecting to a debug card.

## Box Headers

All USB headers are box style, enabling fast connector installation and preventing pin damage.

## Fixed-position Connectors

Connector positions on ASUS Business motherboards remain consistent across product generations, protecting training, manufacturing and investments in supporting hardware.

## Techninė specifikacija

| Procesorius                        |                                                                                                          |
|------------------------------------|----------------------------------------------------------------------------------------------------------|
| Procesoriaus gamintojas            | Intel                                                                                                    |
| Procesoriaus lizdas                | LGA 1700                                                                                                 |
| Procesorių suderinamumas           | „Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, „Intel® Pentium®“ |
| Maksimalus SMP procesorių skaičius | 1                                                                                                        |
| Atmintis                           |                                                                                                          |
| Palaikomi atminties tipai          | DDR4-SDRAM                                                                                               |
| Atminties angų skaičius            | 2                                                                                                        |

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| Maksimali vidinė atmintis               | 64 GB                             |
| Atminties angų tipas                    | SO-DIMM                           |
| Atminties kanalai                       | Dviejų kanalų                     |
| ECC suderinamumas                       | Ne-ECC                            |
| Palaikomi atminties laikrodžio greičiai | 2133,2400,2666,2800,2933,3200 MHz |
| Nebuferizuota atmintis                  | Taip                              |

#### Duomenų laikymo valdikliai

|                                         |               |
|-----------------------------------------|---------------|
| Palaikomi saugojimo kaupiklių sąsajos   | M.2, SATA III |
| Palaikomi saugojimo kaupiklių tipai     | HDD & SSD     |
| Palaikomų saugojimo tvarkyklių skaičius | 3             |

#### Grafika

|                                             |              |
|---------------------------------------------|--------------|
| Paralelinio apdorojimo technologijos parama | Nepalaikomas |
|---------------------------------------------|--------------|

#### Vidinis I/O

|                                  |      |
|----------------------------------|------|
| USB 2.0 jungtys                  | 3    |
| USB 3.2 (3.1 1 kart.) jungtys    | 1    |
| USB 3.2 (3.1 2 kart.) jungtys    | 0    |
| SATA III jungčių skaičius        | 2    |
| Priekinio skydelio audio jungtis | Taip |
| ATX maitinimo jungtis            | Taip |
| CPU fan jungtis                  | Taip |
| Šasi intruzijos jungtis          | Taip |
| COM jungčių skaičius             | 1    |
| TPM jungtis                      | Taip |

#### Galinė panelė I/O jungtys

|                                                        |     |
|--------------------------------------------------------|-----|
| USB 2.0 portų kiekis                                   | 2   |
| USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius         | 2   |
| USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius         | 0   |
| USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius | 0   |
| USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius | 0   |
| Ethernet LAN (RJ-45) portų kiekis                      | 1   |
| VGA (D-Sub) portų kiekis                               | 0   |
| HDMI portų kiekis                                      | 1   |
| HDMI versija                                           | 2.1 |
| „DisplayPort“ kiekis                                   | 1   |

|                                               |                                |
|-----------------------------------------------|--------------------------------|
| „DisplayPort“ versija                         | 1.4                            |
| Tinklas                                       |                                |
| „Wi-Fi“                                       | Ne                             |
| Ethernet LAN jungtis                          | Taip                           |
| Eterneto sąsajos tipas                        | Gigabitinis eternetas          |
| Wake-on-LAN pasirengimas                      | Taip                           |
| „Wi-Fi“ standartas                            | Nepasiekiamo                   |
| Savybės                                       |                                |
| Taikoma                                       | PC                             |
| Motininės plokštės formos faktorius           | Thin Mini ITX                  |
| Motininės plokštės sisteminio valdiklio šeima | Intel                          |
| Pagrindinės plokštės lustas                   | Intel H610                     |
| Garso išvesties kanalai                       | 7.1 kanalai                    |
| Palaikomos „Windows“ operacinės sistemos      | Windows 10 x64, Windows 11 x64 |
| Plėtotės lizdas                               |                                |
| M.2 (M) angų skaičius                         | 1                              |
| BIOS                                          |                                |
| BIOS tipas                                    | UEFI AMI                       |
| BIOS atminties dydis                          | 128 Mbit                       |
| Logistikos duomenys                           |                                |
| Darniosios sistemos (DS) kodas                | 84733020                       |
| Svoris ir matmenys                            |                                |
| Plotis                                        | 170 mm                         |
| Ilgis                                         | 170 mm                         |
| Aukštis                                       | 221 mm                         |
| Pakuotės turinys                              |                                |
| Pridėti kabeliai                              | SATA                           |
| Tvarkyklės įskaitytos                         | Taip                           |
| Kitos savybės                                 |                                |
| Svoris                                        | 382 g                          |

## Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

## Gamintojo ir saugos informacija

### GAMINTOJAS

#### ASUSTeK Computer Inc

Li-Te Road 15, 112 Taipei, TW

[asus.com](https://asus.com)

### ATSAKINGAS ASMUO ES

#### ASUS France S.A.R.L.

Allee bienvenue 10, 93160 Paris, FR

[channel.asus.com](https://channel.asus.com)

### PLATINTOJAS

#### MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](mailto:info@shopro.lt)