

Lindy 65W USB 2 x Type C GaN Charger

Gamintojas: **LINDY** · Modelis: **73438** · EAN: **4002888734387** · Prekės kodas: **724760**



39,91 €

Kaina su PVM

Be PVM: **32,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Charges and powers two devices simultaneously via 2 USB Type C ports
- ✓ 65W GaN technology via the USB Type C ports provides fast charging for smartphones, tablets, laptops and other mobile devices
- ✓ Compact design for maximum mobility
- ✓ Built-in safety features such as overvoltage and overcurrent protection



Aprašymas

The Lindy 65W 2 x USB Type-C GaN Charger, a powerful and compact charging solution designed to meet the demands of modern devices. Utilizing advanced Gallium Nitride (GaN) technology, this charger delivers efficient, high-speed charging in a much smaller and lighter form factor compared to traditional chargers.

GaN is a semiconductor material that has revolutionized the design and performance of modern chargers. Unlike traditional silicon-based chargers, GaN chargers can operate at higher voltages and temperatures, allowing for faster and more efficient power delivery. This efficiency enables the components inside the charger to be closer together, resulting in a significantly smaller and more portable charger without compromising on power or performance. GaN technology not only enhances the charger's efficiency but also reduces energy loss and heat generation, making it a more sustainable and reliable choice for powering your devices.

The charger also supports Quick Charge 4.0 (QC 4.0), ensuring that compatible devices charge faster than ever. With dual USB Type-C ports, this charger allows you to simultaneously charge two devices, such as smartphones, tablets, laptops. The 65W output ensures fast and reliable charging,

making it ideal for quickly powering up your devices, whether you're at home, in the office, or on the go. 65W Power Delivery (PD) and Programmable Power Supply (PPS) are supported by the USB Type C ports. When both ports are in use a maximum of 65W will be split between both of the ports. 45W will be provided to the C1 port whilst only 20W will be provided to the C2 port.

The charger's intelligent power distribution automatically adjusts the power output to each connected device, optimizing the charging speed while ensuring safety. Built with multiple safety features, including overcurrent, overvoltage, and short-circuit protection, you can charge your devices with peace of mind. Support for PPS allows the charger to dynamically adjust its output voltage and current to match the specific needs of the connected device. This ensures optimal charging efficiency and helps protect the battery life of your devices.

Compact, lightweight, and travel-friendly, the 65W 2 x USB Type-C GaN Charger is the perfect companion for those who need reliable and efficient charging on the move. Upgrade your charging experience with this state-of-the-art GaN charger, designed to keep up with your fast-paced lifestyle.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook Chargers [+263][-61]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	2
USB Type-C ports quantity	2
Fast charging	Yes
Fast charging technology	Power Delivery 3.0
Programmable power supply (PPS)	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	65 W
Power protection features	Over current, Over voltage, Overheating, Short circuit
Compatibility	CE, RoHS, REACH, ErP
Design	
Product colour	Black
Housing material	Polyvinyl chloride (PVC), Polycarbonate (PC)
Connector material	Copper
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Input current	1.5 A

Maximum power	65 W
Maximum output voltage	20 V
Minimum output voltage	5 V
Output voltage accuracy (±)	5%
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	3 A
Output current (15V)	3 A
Output current (20V)	3.25 A
Power consumption (no load)	0.1 W
Average active efficiency	81.38%
Efficiency at low load (10%)	Yes
Weight & dimensions	
Width	26.8 mm
Depth	85.3 mm
Height	41.6 mm
Weight	40 g
Packaging data	
Package width	80 mm
Package depth	100 mm
Package height	45 mm
Package weight	60 g
Package type	Carton
Operational conditions	
Operating temperature (T-T)	0 - 25 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%
Packaging content	
Quantity per pack	1 pc(s)
Manual	Yes
Certificates	
Compliance certificates	CE, REACH, RoHS
Sustainability	

Sustainability certificates	ErP
-----------------------------	-----

Sustainability compliance	Yes
---------------------------	-----

Logistics data

Warranty period	2 year(s)
-----------------	-----------