

EIZO FlexScan S1934H-GY computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LCD Grey

Gamintojas: **EIZO** · Modelis: **S1934H-GY** · EAN: **4995047049227** · Prekės kodas: **724861**



381,90 €

Kaina su PVM

Be PVM: **315,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48.3 cm (19") LCD IPS
- ✓ 60 Hz 14 ms 250 cd/m² 1000:1
- ✓ SXGA 1280 x 1024 pixels 5:4
- ✓ C 9 kWh 9.4 W



Aprašymas

Optimized Brightness with Auto EcoView

The Auto EcoView function is a sensor on the front of the monitor that measures ambient light and optimizes the screen's brightness to a level akin to viewing a sheet of paper under typical office lighting conditions. Since the screen is never too bright, eye strain is reduced while power consumption is cut by up to 50% compared to operating the monitor with Auto EcoView turned off and set to the default factory brightness of 100%.

IPS Panel with Wide Viewing Angles

The IPS (in-plane switching) panel offers 178° viewing angles to minimize color shift and contrast when viewing the screen at an angle. This ensures stable and consistent display when two or more people view the screen at once or in a multi-monitor environment.

Three Inputs Including DisplayPort

DisplayPort, DVI-D 24-pin, and D-Sub mini 15-pin inputs are included for connection with various graphics boards.

Viewing Comfort with an Ergonomic Stand

Adjust the screen to the most comfortable position with 100 mm height adjustment, 30° tilt, 70° swivel, and 90° rotation for portrait mode. A stand with 30° tilt only is available as an option.

Reduced Blue Light

A preset mode called “Paper” adjusts the brightness, contrast ratio, and color temperature to simulate those of printed paper. Paper mode significantly reduces the amount of blue light emitted from the screen for more comfortable viewing.

Built to Last Five Years

EIZO's five-year warranty is two years or 67% longer than the standard three-year warranty of most brands. Even if the initial purchase price of the FlexScan S1934 is higher than another 19-inch monitor, the TCO (total cost of ownership) will likely be lower due to the significantly longer buying cycle and less need for repair.

Optional LCD Panel Protector

The FP-1901 protector fits easily between the LCD screen and bezel, has a light transmission rate of more than 90%, and includes both an anti-glare coating side to reduce light reflection and a glossy side for crisper, more vibrant images.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitors [+653][-245]
Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LCD
Touchscreen	No
HD type	SXGA
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	16.78 million colours
LED backlight	Yes
Backlight type	W-LED

Display brightness (typical)	250 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	1280 x 1024 (SXGA)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.293 x 0.293 mm
Pixel density	87 ppi
Horizontal scan range	31 - 64 kHz
Vertical scan range	55 - 61 Hz
Viewable size, horizontal	37.5 cm
Viewable size, vertical	30 cm
Viewable size diagonal	48.1 cm
Colour gamut standard	sRGB
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
Design	
Market positioning	Office
Product colour	Grey
Feet colour	Grey
Ports & interfaces	
Built-in USB hub	No
HDMI	No
Headphone out	Yes
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
DisplayPorts quantity	1
Headphone outputs	1

Headphone connectivity	3.5 mm
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	No
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Adjustable height (max)	10 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	-35 - 35°
Tilt adjustment	Yes
Tilt angle range	0 - 30°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Swedish
Number of OSD languages	9
Power	
Energy efficiency class (SDR)	C
Energy consumption (SDR) per 1000 hours	9 kWh
Power consumption (typical)	9.4 W
Power consumption (standby)	0.5 W
Power consumption (max)	21 W
Power consumption (off)	0.1 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	405 mm

Depth (with stand)	205 mm
Height (with stand)	506.5 mm
Weight (with stand)	5.6 kg
Width (without stand)	405 mm
Depth (without stand)	61.5 mm
Height (without stand)	334 mm
Weight (without stand)	3.8 kg
Packaging content	
Stand included	Yes
Cables included	AC, Audio (3.5mm), DVI, VGA
Quick start guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Other features	
Automatic brightness control	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	10
Certification	TCO, TUV/GS, RCM, CE, CB, cTUVus, FCC-B, ICES-003-B, TUV/S, VCCI-B, EPA Energy Star, RoHS, WEEE, RoHS, CCC, EAC
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	21,00cm × 41,00cm × 41,00cm
Svoris	5,60kg