LG 50UL5Q-E Signage Display Digital signage flat panel 127 cm (50") LED Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS 24/7

Gamintojas: **LG ELECTRONICS** · Modelis: **50UL5Q-E** · EAN: **8806096602140** · Prekės kodas: **725106**

552,90 €

Kaina su PVM

Be PVM: **456,94 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Resolution : 3,840 × 2,160 (UHD)
- ✓ Brightness : 500 nit (Typ.)
- ✓ 24Hr Usage Scene (24 Hours / 7 Days)
- ✓ Face Up/Down with Tilt Support
- ✓ Even Bezel
- ✓ High-Performance with webOS 6.1

Aprašymas

Superb Picture Quality with Ultra HD Resolution
The UL5Q-E series, with UHD resolution, enhances the realism of colors and details in the content. Its wide viewing angle offers clear visuals, while its 500-nit brightness vividly showcases the content.

High-Performance with LG webOS 6.1
LG webOS 6.1 is available on the UL5Q-E series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI.

Even Bezel Design
The UL5Q-E series features even bezels, enhancing the aesthetic appeal of various spaces. These uniform bezels not only facilitate easy installation but also transform standard displays into elegant focal points.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Adaptive Viewing Experience
Experience the flexibility with the UL5Q-E series' up/down tilt capability. Whether mounted high or low, the display can be adjusted to eye level, offering viewer engagement regardless of installation height. This versatility not only enhances spatial efficiency but also provides visual comfort, delivering clear information from various viewing angles.

Engineered for 24/7 Operation
Built for environments that never sleep, the UL5Q-E series features panel technology that enables 24/7 operation.

Built-In Brightness Sensor
The UL5Q-E series' front-mounted brightness sensor automatically adjusts brightness to match various lighting conditions, optimizing viewing quality and energy efficiency without manual intervention. This adaptive feature offers consistent display performance while also supporting power optimization, delivering a visual experience that dynamically responds to environmental changes.

Advanced Security Architecture
The UL5Q-E series incorporates LG’s Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/ IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today’s challenging security landscape.

Remote Monitoring and Control
This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anytime, anywhere from their mobile phone & PC in a network-accessible environment, with access to both current and past data. It allows the user to monitor the unit, make adjustments, and control the unit remotely in real time.

EPEAT Registered
The Electronic Product Environmental Assessment Tool (EPEAT) is a method for several layers of customers to evaluate the effect of a product on the environment. UL5Q-E series is an EPEAT Bronze-certified* display which means that it meets all the required criteria in the Computers and Displays category.

LG ConnectedCare
Maintenance is easy and fast with the optional LG ConnectedCare* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitors [+653][-245]
Display	
Display diagonal	127 cm (50")
Display technology	LED
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	VA
Native aspect ratio	16:9

Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Colour saturation	80%
Rated lifetime	30000 h
Native refresh rate	60 Hz
Haze rate	25%
Ports & interfaces	
HDMI ports quantity	3
USB port	Yes
HDMI version	2.2/1.4
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
PC Audio out	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	200 x 200 mm
Bezel width (bottom)	1.08 cm
Bezel width (side)	1.08 cm
Bezel width (top)	1.08 cm
Bezel colour	Black
Performance	
Purpose	Commercial

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Operating hours (hours/days)	24/7
Web browser	Yes
webRTC support	Yes
Power	
Power consumption (typical)	115 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
Power consumption (economy mode)	0.5 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	112 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Internal memory	8 GB
Operating system installed	WebOS
Operating system version	6.1
Weight & dimensions	
Display width	1120.2 mm
Display depth	59.9 mm
Display height	641.4 mm
Display weight	9.3 kg
Packaging data	
Package width	1125 mm
Package depth	760 mm
Package height	118 mm
Package weight	12.2 kg
Packaging content	
Remote control included	Yes
Cables included	Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Operating relative humidity (H-H)	10 - 80%
Sensors	
Gyroscope	Yes
Temperature sensor	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Technical details	
Compliance certificates	CB, CE, Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC)
Other features	
Power supply type	Internal
Matmenys ir svoris	
Matmenys (I × P × A)	76,00cm × 126,00cm × 12,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903