

ICY BOX IB-3740-C31 HDD/SSD enclosure Black 2.5/3.5"

Gamintojas: **ICY BOX** · Modelis: **IB-3740-C31** · EAN: **4250078167044** · Prekės kodas: **725158**



204,90 €

Kaina su PVM

Be PVM: **169,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **EFFICIENT ENCLOSURE:** The external JBOD enclosure offers space for four SATA III hard drives in 2.5" or 3.5" format. The enclosure is simply powered with the included 60W power supply
- ✓ **TOP SPEED:** The enclosure is connected to the PC via USB 3.1 (Gen 2) and thus enables transfer speeds of up to 10 Gbit/s. A USB-C connector is included. A USB-C connector is included
- ✓ **SINGLE MODE:** Each drive is recognised individually so that all HDDs/SSDs can be accessed separately. The enclosure is supported by both Windows and MacOS
- ✓ **STATUS LED:** Via the LED display you can see at any time which hard disk is being accessed or whether there are errors. The synchronised standby mode also saves energy
- ✓ **OPTIMAL COOLING:** The 80 mm fan (3 levels of temperature control) ensures sufficient cooling of the hard disks. It optimally dissipates the heat generated from the enclosure



Aprašymas

It's the mix

Apart from the improved design, the advantage of the IB-3740-C31 is that it can support 2.5" and 3.5" drives. This makes the device an ideal candidate for users looking for the maximum amount of direct-attached storage space since traditional spinning disks can accommodate a significantly larger amount of data than the largest solid-state drives. If you're looking to eke out maximum performance, however, you'll want to use 2.5" SSDs instead.

For the environment

When the host device is not being used or if the data transfer cable is not connected the IB-3740-C31 turns itself into standby mode automatically. In addition, each drive bay has an LED indicator in order to provide information regarding HDD activity (read/write), fan settings, and sync status.

Fast data transfer

The connection between the host PC and the external enclosure is realized by a USB 3.1 Type-C™ port. Thanks to the USB 3.1 (Gen 2) protocol a high data transfer rate of up to 10 Gbit/s can be achieved.

Techninė specifikacija

Specifications	
Sandėlio grupė	Storage [+57][−7]
Storage	
Storage drive size	2.5/3.5"
Supported storage drive interfaces	Serial ATA, Serial ATA II, Serial ATA III
Number of storage drives supported	4
RAID levels	JBOD
Maximum storage capacity	10 TB
Ports & interfaces	
USB connectivity	Yes
USB version	3.2 Gen 2 (3.1 Gen 2)
USB connector type	USB Type-C
USB connector gender	Female
USB ports quantity	1
DC-in jack	Yes
Design	
Product type	HDD/SSD enclosure
Product colour	Black
Material	Aluminium, Plastic
LED indicators	Yes
On/off switch	Yes
Number of fans	1 fan(s)
Fan diameter	8 cm
Performance	
Data transfer rate	10 Gbit/s
Chipset	VIALabs VL820, VL715
UASP support	Yes

Plug and Play	Yes
Country of origin	Taiwan
Power	
Power source type	DC
AC adapter input voltage	100 - 240 V
AC adapter input current	1.6 A
AC adapter frequency	50 - 60 Hz
AC adapter output voltage	12 V
AC adapter output current	5 A
Power consumption (max)	60 W
System requirements	
Windows operating systems supported	Yes
Mac compatibility	Yes
Mac operating systems supported	Yes
Weight & dimensions	
Width	225 mm
Depth	127 mm
Height	170 mm
Weight	2.13 kg
Cable length	1 m
Package width	295 mm
Package depth	160 mm
Package height	270 mm
Package weight	3.43 kg
Packaging content	
Cables included	USB Type-C
Screws included	Yes
Screwdriver included	Yes
Manual	Yes
Logistics data	
Harmonized System (HS) code	84718000
Master (outer) case width	606 mm
Master (outer) case length	503 mm
Master (outer) case height	290 mm

Master (outer) case gross weight	20.6 kg
Products per master (outer) case	6 pc(s)