

Lindy 7 Port USB 3.0 Metal Hub

Gamintojas: **LINDY** · Modelis: **43128** · EAN: **4002888431286** · Prekės kodas: **725529**



150,90 €

Kaina su PVM

Be PVM: **124,71 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Provides 7 USB 3.0 SuperSpeed ports with data rates up to 5Gbps
- ✓ Hard-wearing USB Hub - Perfect for industrial applications
- ✓ Robust metal housing with high EMC protection and integrated brackets for mounting
- ✓ USB bus-powered, or can be externally powered
- ✓ 2 year warranty



Aprašymas

The Lindy 7 Port USB 3.0 Metal Hub has been designed to provide reliable performance in demanding operational environments.

This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for use in industrial environments.

Backwards compatibility with USB 2.0/1.1/1.0 means the hub can simultaneously support older USB peripherals or systems that lack USB 3.0 capabilities, extending their lifetime and giving a greater return on investment. Each port features individual short circuit protection, while the included power supply ensures secure and uninterrupted electricity supply. Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface. USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support

data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+541][-77]
Ports & interfaces	
Hub interfaces	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	7
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
LED indicators	Yes
Cable length	0.8 m
Weight & dimensions	
Width	185 mm
Depth	75 mm
Height	20 mm
Weight	379 g
Packaging content	
Cables included	USB
Operational conditions	
Operating temperature (T-T)	0 - 65 °C
Logistics data	
Harmonized System (HS) code	84719000