EIZO FlexScan EV3450XC-BK computer monitor 86.6 cm (34.1") 3440 x 1440 pixels UltraWide Quad HD LCD Black

Gamintojas: **EIZO** · Modelis: **EV3450XC-BK** · EAN: **4995047067368** · Prekės kodas: **725663**

1 037,90 €

Kaina su PVM

Be PVM: **857,77 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 34.1"" curved ultrawide monitor with 21:9 format and 3440x1440 pixels (109 ppi) for excellent readability
- ✓ 5 MP webcam, microphone with noise canceling, integrated speaker and audio connection
- ✓ Docking function via USB-C with DisplayPort signal, LAN and power supply up to 94 watts
- ✓ Signal inputs: USB-C (DisplayPort Alt Mode), DisplayPort, dual HDMI
- ✓ Auto EcoView, EcoView Index and EcoView Optimizer for maximum energy savings and optimum ergonomics
- ✓ KVM switch and picture-in-picture operation for up to 2 computers/signal sources
- ✓ Optionally in black or white housing color
- ✓ Demonstrably environmentally conscious and socially responsible production
- ✓ 5-year warranty for maximum investment security

Aprašymas

The EIZO FlexScan EV3450XC is optimized for the demands of the modern working world. With an integrated, high-resolution 5MP webcam, built-in microphone with noise and echo cancellation and feedback-free speakers, it is fully equipped for video conferencing. In addition, the curved ultrawide screen with a 34.1" diagonal, 21:9 format and UWQHD resolution (3440 x 1440 pixels) offers an extra large screen area for demanding applications or intensive multitasking. The webcam and infrared sensor support Windows Hello for convenient and secure unlocking of the computer

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

using facial recognition. The EV3450XC's USB-C docking connects video, audio and USB data signals and charges laptops with 94 watts of power. The integrated LAN port enables stable online conferences. Image reproduction with the EV3450XC is sharp, clear, fast and flicker-free. When scrolling and positioning windows or images, the readable display appears in fractions of a second - faster than it can be perceived. Power consumption and energy efficiency are always in view. This also applies to colors, which are displayed in sRGB free of oversaturation. Equipped in this way, the EV3450XC is ideally tailored to the challenges of companies that rely on hybrid forms of work with a combination of office work and remote work.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitors [+653][-245]
Display	
Display diagonal	86.6 cm (34.1")
Display resolution	3440 x 1440 pixels
Native aspect ratio	21:9
Display technology	LCD
Touchscreen	No
HD type	UltraWide Quad HD
Panel type	IPS
Response time	5 ms
Screen shape	Curved
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	300 cd/m²
Anti-glare screen	Yes
Screen curvature rating	3800R
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440, 3440 x 1440
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Pixel density	109 ppi
Viewable size, horizontal	80 cm
Viewable size, vertical	33.5 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Digital horizontal frequency	31 - 89.5 kHz
Digital vertical frequency	29.5 - 61 Hz
Display diagonal (metric)	86.7 cm
Colour gamut standard	sRGB
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	Yes
Number of speakers	2
RMS rated power	8 W
Megapixel (approx.)	5 MP
Built-in microphone	Yes
Design	
Market positioning	Office
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	94 W

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

HDMI ports quantity	2
DisplayPorts quantity	1
Headphone outputs	1
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes
HDCP	Yes
HDCP version	1.4/2.3
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Adjustable height (max)	19.5 cm
Swivelling	Yes
Swivel angle range	-90 - 90°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Power	
Energy efficiency class (SDR)	F
Energy consumption (SDR) per 1000 hours	25 kWh
Power consumption (typical)	23 W
Power consumption (standby)	0.4 W
Power consumption (max)	222 W
Power consumption (off)	0 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%

Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	819.5 mm
Depth (with stand)	242 mm
Height (with stand)	414.5 mm
Weight (with stand)	12.1 kg
Width (without stand)	819.5 mm
Depth (without stand)	103.1 mm
Height (without stand)	385 mm
Weight (without stand)	9.2 kg
Packaging content	
Stand included	Yes
Cables included	AC, DisplayPort, USB Type-C to USB Type-C, USB Type-A to USB Type-B
Quick start guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
Sustainability compliance	Yes
Other features	
Picture-by-Picture (PbP)	Yes
Automatic brightness control	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	14
Compliance certificates	CB, CCC, CE, China RoHS, Federal Communications Commission (FCC), GS mark, PSE, RCM, RoHS, TÜV mark, UKCA, VCCI
Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports	1
Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 10, TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, China RoHS, CCC, EPEAT 2018 Gold (US), EPEAT Climate +
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	96,00cm × 50,00cm × 34,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903