

CyberPower VP700ELCD uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 390 W 4 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **VP700ELCD** · EAN: **4712856274844** · Prekės kodas: **726719**



134,90 €

Kaina su PVM

Be PVM: **111,49 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Generator Compatible
- ✓ Automatic Voltage Regulation (AVR)
- ✓ High-speed Ethernet Data Transmission
- ✓ Surge and Spike Protection
- ✓ PowerPanel Management Software
- ✓ Energy Saving Technology
- ✓ Simulated Sine Wave Output
- ✓ LCD Status Display
- ✓ USB Connectivity Port



Aprašymas

VP700ELCD

CyberPower VP700ELCD offers home and office users a reliable battery backup and safeguards office PCs and other electronic devices from surges, spikes, brownouts and other power incidents. Designed with GreenPower UPS Technology to improve operating efficiency and to minimize energy consumption, users can enjoy significant energy cost savings over conventional UPS systems. The UPS provides Automatic Voltage Regulation (AVR) to maintain safe voltage for connected equipment. The UPS provides multifunctional LCD readout to display clear power and battery conditions. The product features data line protection with high-speed transmission to safeguard phones, network and communication equipment against surge/spike as well as supply 1Gbps speed to transmit data. The UPS is also compatible with PowerPanel Power Management Software to achieve real-time

monitoring and configuration.

Techninė specifikacija

Specifications	
Sandėlio grupė	Unterbrechungsfreie Stromversorgung [+38] [-106]
Features	
UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	390 W
Waveform	Sine
Input operation voltage (min)	167 V
Input operation voltage (max)	295 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	Yes
Maximum current	3.04 A
Surge energy rating	450 J
Response time	4 ms
Heat dissipation	9.5 BTU/h
Number of input phases	1
Number of output phases	1
EMI/RFI noise filtering	Yes
Noise level	40 dB
Surge protection	Yes
Power protection features	Over voltage
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
Power plug	C14 coupler
AC outlets quantity	4 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1

USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Ethernet LAN (RJ-45) ports	2
Cabling technology	10/100/1000Base-T(X)
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	1 min
Typical backup time at half load	10 min
Battery recharge time	8 h
Design	
Form factor	Tower
Product colour	Black
Housing material	Plastic
Cable length	1.5 m
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Certificates	
Compliance certificates	RoHS
Certification	CE, RCM
Packaging content	
Cables included	USB cable
Manual	Yes
Weight & dimensions	
Width	100 mm

Depth	260 mm
Height	227 mm
Weight	5.14 kg
Packaging data	
Package width	300 mm
Package depth	143 mm
Package height	335 mm
Package weight	5.76 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	35,00cm × 31,00cm × 33,00cm
Svoris	12,01kg