

Epson EB-2250U Standard throw projector 5000 ANSI lumens 3LCD WUXGA (1920x1200) White

Gamintojas: **EPSON** · Modelis: **V11H871040** · EAN: **8715946628646** · Prekės kodas: **726854**



1 038,91 €

Kaina su PVM

Be PVM: **858,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Standard throw projector White
- ✓ 3LCD 5000 ANSI lumens
- ✓ Lamp 5000 h
- ✓ WUXGA (1920x1200) 16:10 15000:1
- ✓ Screen size compatibility: 1270 - 7620 mm (50 - 300") Number of colours: 1.07 billion colours
- ✓ Focus: Manual
- ✓ Ethernet LAN
- ✓ Built-in speaker(s) 16 W
- ✓ AC 405 W

Aprašymas

Our super-bright new business projector offers an outstanding brightness 5,000 lumens and full HD resolution. The EB-2250U is designed to project a scalable image size of up to a 300 inches, and offers connectivity options such as dual HDMI and optional Wi-Fi.

Outstanding quality display of up to 300 inches

Full HD resolution combined with Epson's 3LCD technology ensures high-quality content has more vivid colours and brighter images. HDMI connectivity guarantees sharper and clearer presentations delivered on a scalable image size of up to 300 inches.

Simple setup and connectivity

The EB-2250U offers a wide range of connectivity options, including screen mirroring, wireless LAN (optional) and two HDMI inputs. Setup is easy too, thanks to features including auto-power-on, focus help, keystone correction and screen fit - delivering presentations quickly and efficiently.

Keep costs down

Project for longer with improved reliability and a longer lamp life of up to 10,000 hours in eco mode.

Home screen

The home screen offers quick and easy access to a variety of useful functions, such as connection sources. Wireless connections can also be made easily using the information on screen.

Gesture Presenter

Change slides by simply moving your hand, making even smarter presentations a reality by liberating the user from their remote control or mouse.

Value-added flexibility

Techninė specifikacija

Specifications	
Sandėlio grupė	Projectors [+20][-22]
Projector	
Projector brightness	5000 ANSI lumens
Projection technology	3LCD
Projector native resolution	WUXGA (1920x1200)
Contrast ratio (typical)	15000:1
Native aspect ratio	16:10
Screen size compatibility	1270 - 7620 mm (50 - 300")
Projection distance	1.5 - 9 m
Projection distance (wide)	0 - 1.5 m
Projection distance (tele)	0 - 9 m
Contrast ratio (dynamic)	15000:1
Number of colours	1.07 billion colours
Projector brightness (economic mode)	3800 ANSI lumens
Vertical scan range	200 - 240 Hz
Keystone correction, horizontal	-20 - 20°
Keystone correction, vertical	-30 - 30°
Matrix size	1.93 cm (0.76")
Matrix type	3-panel (p-Si TFT active)
Light source	
Light source type	Lamp
Service life of light source	5000 h
Service life of light source (economic mode)	10000 h

Lamp power	300 W
Lamps quantity	1 lamp(s)
Lens system	
Focus	Manual
Focal length range	23 - 38.4 mm
Aperture range (F-F)	1.5 - 2
Zoom type	Manual
Zoom ratio	1.6:1
Digital zoom	1.6x
Throw ratio	1.38 - 2.28:1
Video	
Full HD	Yes
3D	No
Video processing	10 bit
Colour modes (2D)	Cinema, Dynamic
Video colour modes	Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM simulation mode
Ports & interfaces	
VGA (D-Sub) ports quantity	3
HDMI ports quantity	2
Composite video in	1
Component video (YPbPr/YCbCr) in	3
DVI port	No
Audio (L/R) in	0
Serial interface type	RS-232C
S-Video inputs quantity	0
USB 2.0 ports quantity	2
USB 2.0 Type-B ports quantity	1
PC Audio in	Yes
PC Audio out	Yes
Mobile High-Definition Link (MHL)	Yes
AC (power) in	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No

Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Storage	
Card reader integrated	No
Features	
Noise level	39 dB
Noise level (economic mode)	29 dB
Country of origin	Philippines
Password protection	Yes
Multimedia	
Built-in speaker(s)	Yes
RMS rated power	16 W
Design	
Product type	Standard throw projector
Product colour	White
Placement	Ceiling, Desktop
Cable lock slot	Yes
Cable lock slot type	Kensington
Display	
Built-in display	No
Power	
Power source	AC
Power consumption (typical)	405 W
Power consumption (standby)	0.5 W
Power consumption (economy mode)	323 W
AC input voltage	220-240 V
AC input frequency	50 - 60 Hz
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Weight	4.6 kg

Width	377 mm
Depth	291 mm
Height	110 mm
Package width	383 mm
Package depth	530 mm
Package height	210 mm
Package weight	6.4 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI
Manual	Yes
Bundled software	EasyMP Monitor, EasyMP Multi PC Projection
Technical details	
Sustainability certificates	TCO
Logistics data	
Quantity per pack	1 pc(s)
Products per pallet	40 pc(s)
Pallet gross weight	0 g
Pallet gross length	120 cm
Pallet gross width	80 cm
Pallet gross height	3.5 m
Products per pallet layer	4 pc(s)
Products per pallet layer (UK)	5 pc(s)
Products per pallet (UK)	50 pc(s)
Pallet weight (UK)	0 g
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	3.5 m
Harmonized System (HS) code	85286200
Other features	
RS-232 ports	1
RS-232C	Yes
Matmenys ir svoris	

Matmenys (I × P × A)	52,00cm × 38,00cm × 20,00cm
Svoris	6,47kg