

HP Series 7 Pro 34 inch WQHD Conferencing Monitor - 734pm

Gamintojas: HP · Modelis: 8K157UT#ABB · EAN: 198415143440 · Prekės kodas: 726915



1 051,90 €

Kaina su PVM

Be PVM: 869,34 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Collaborate like you're face to face thanks to the stunningly realistic Poly Studio AI webcam and audio with effortless AI experiences across any OS.
- ✓ With WQHD resolution and a superfast Thunderbolt™ 4 connection, you have the simplicity and power you need for maximum productivity.
- ✓ Reimagine what's possible thanks to factory-calibrated color accuracy on an IPS Black HDR400 monitor with 98% Display P3 for billions of realistic colors.
- ✓ Thoughtfully made with at least 90% recycled plastic content and 90% recycled aluminum in the stand.

Aprašymas

Intelligent conferencing, ahead of the curve

Effortlessly make a great impression with built-in AI on the HP 34" WQHD Conferencing Monitor. Intelligent conferencing delivers productive, high-quality collaboration every time. And it's all on a dazzling ultrawide display with powerful Thunderbolt™ 4.

Techninė specifikacija

Display	
Display diagonal	86.4 cm (34")
Display resolution	3440 x 1440 pixels
Native aspect ratio	21:9
Display technology	LCD

Touchscreen	No
HD type	Wide Quad HD
Panel type	IPS Black
Response time	5 ms
Screen shape	Curved
Contrast ratio (typical)	2000:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	Edge LED
Display brightness (typical)	400 cd/m²
Display brightness	400 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Anti-glare screen	Yes
Screen curvature rating	1900R
Supported graphics resolutions	1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1440 x 900 (WXGA+), 1600 x 1200 (UXGA), 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440, 3440 x 1440, 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA)
Aspect ratio	21:9
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.23 x 0.23 mm
Pixel density	109 ppi
Horizontal scan range	30 - 190 kHz
Vertical scan range	30 - 120 Hz
Viewable size, horizontal	80 cm
Viewable size, vertical	33.5 cm
Display diagonal (metric)	86.4 cm
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	DisplayHDR 400
Haze rate	25%
Surface hardness	3H
Colour depth	8 bit
Colour gamut standard	sRGB, DCI-P3

Colour gamut	100%
sRGB coverage (typical)	100%
DCI-P3 coverage	98%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	Yes
AMD FreeSync type	FreeSync Premium
Fast charging	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes
HP segment	Business
Infrared (IR) sensor	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	Yes
Number of speakers	4
RMS rated power	12 W
Megapixel (approx.)	5 MP
Built-in microphone	Yes
Audio decoders	DTS Virtual:X
Design	
Market positioning	Business
Product colour	Black, Silver
Detachable stand	Yes
Feet colour	Silver, Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	3.2 Gen 2 (3.1 Gen 2)
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	5
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes

USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
HDMI ports quantity	1
HDMI version	2
DisplayPorts quantity	1
DisplayPort out quantity	1
DisplayPort out version	1.4
DisplayPort version	1.4
Thunderbolt 4 ports quantity	2
Microphone in	Yes
Built-in KVM switch	Yes
HDCP	Yes
Network	
Ethernet LAN	Yes
Remotely operated	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Adjustable height (max)	15 cm
Swivelling	Yes
Tilt adjustment	Yes
Tilt angle range	-5 - 20°
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	G
Energy consumption (SDR) per 1000 hours	32.5 kWh
Energy consumption (HDR) per 1000 hours	68 kWh
Power consumption (typical)	51 W
Power consumption (standby)	0.5 W
Power consumption (max)	310 W
Power consumption (off)	0.3 W

AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	813.8 mm
Depth (with stand)	266.9 mm
Height (with stand)	547.4 mm
Weight (with stand)	11.3 kg
Width (without stand)	813.8 mm
Depth (without stand)	120.2 mm
Height (without stand)	364.1 mm
Weight (without stand)	8.78 kg
Packaging data	
Package width	952 mm
Package depth	226 mm
Package height	485 mm
Package weight	17.4 kg
Package type	Box
Warranty card	Yes
Packaging content	
Cables included	HDMI, DisplayPort, Thunderbolt, USB Type-C to USB Type-A, AC
Quick start guide	Yes
Bundled software	HP Display Center; HP Client Management Script Library
Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT, TCO, EPEAT Climate +, TCO10

Sustainable technologies and materials	Low halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; 90% post-consumer recycled plastic; Made with 15% recycled steel; 90% recycled aluminum
Sustainability compliance	Yes
Other features	
Country of origin	China
Packaging content	Monitor; Thunderbolt™ cable; DisplayPort™ cable; HDMI cable; Warranty card; Quick Setup Poster; 1 USB Type-C to Type-A cable; AC power cord; Color calibration report; VESA mount adapter
Weight	11.3 kg
Height	364.1 mm
Width	813.8 mm
Depth	120.2 mm
Compliance certificates	CECP, CCC, CB, EAC, BIS, Federal Communications Commission (FCC), CE, BSMI
Low halogen	Yes
Ethernet LAN (RJ-45) ports	1
Certification	BIS; BSMI; CB; CCC; CE; CECP; CEL; EAC; FCC; ISO 9241-307; KC; KCC; NOM; PSB; RCM; SEPA; TUV-S; UL/CSA; VCCI; WEEE; ISC; Low blue light; WW application; ICE; UAE; GS; Ukraine EE; Belarus EE; Korea MEPS; CEL Grade 2
UNSPSC-code	43211902
Supplied AC adapter type	198415143471
Technical details	
General Product Safety Regulation (GPSR) URL	https://support.hp.com/us-en/document/ish_6126692-6126777-16?openCLC=true
Matmenys ir svoris	
Matmenys (I × P × A)	95,00cm × 23,00cm × 49,00cm
Svoris	17,40kg