

iiyama ProLite TF2415MC-B2 kompiuterio monitorius 60,5 cm (23.8") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Daugybė naudotojų Juoda

Gamintojas: **IYYAMA** · Modelis: **TF2415MC-B2** · EAN: **4948570116775** · Prekės kodas: **726936**



594,90 €

Kaina su PVM

Be PVM: **491,65 €**

[Sandėlyje](#)




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 60,5 cm (23.8") Juoda
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Reakcijos laikas: 16 ms
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: VA
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CB, CE, cULus, REACH, RoHS, WEEE





Aprašymas

The ProLite TF2415MC-B2 (23.8 inch) uses PCAP touch technology and is built into an eye-catching bezel with edge-to-edge glass. Thanks to a glass overlay covering the screen and a rugged bezel, it guarantees high durability and scratch-resistance, making it perfect for kiosk and high use public facing applications. Equipped with a foam seal finish it supports seamless integration into kiosks and provides IP65 rating resulting in dust and water resistance from the front. Landscape, portrait and face-up orientation ensures flexible mounting possibilities in almost any installation. For ease of integration, the TF2415MC-B2 can be equipped with optional external mounting brackets (OMK2-1) making it an ideal solution for kiosk integrators, industrial environments, control rooms and interactive multimedia.

Techninė specifikacija

Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	VA
Response time	16 ms
Screen shape	Flat
Contrast ratio (typical)	3000:1
Display number of colours	16.78 million colours
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	350 cd/m²
Display brightness	315 cd/m²
Aspect ratio	16:9
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2745 x 0.2745 mm

Horizontal scan range	31.4 - 82 kHz
Vertical scan range	56 - 75 Hz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
Surface hardness	7H
Separate H/V sync	Yes
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
OmniTapps Multitouch compatibility	No
Multimedia	
Built-in camera	No
Built-in microphone	No
Design	
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Audio output	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7
Plug and Play	Yes
Power	

Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	22 kWh
Power consumption (typical)	24.4 W
Power consumption (standby)	1.06 W
Power consumption (off)	0.32 W
AC adapter output voltage	12 V
Power supply type	External
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width (with stand)	575 mm
Depth (with stand)	42.5 mm
Height (with stand)	347 mm
Weight (with stand)	5.8 kg
Width (without stand)	575 mm
Depth (without stand)	42.5 mm
Height (without stand)	347 mm
Weight (without stand)	5.8 kg

Packaging content

Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes

Sustainability

Sustainability certificates	ErP
-----------------------------	-----

Other features

International Protection (IP) code	IP65
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
AC adapter included	Yes
Display viewable area (HxV)	527.04 x 296.46 mm
Placement supported	Horizontal/Vertical

Brightness	315 cd/m²
Packaging content	AC adapter, Touch Panel Driver Disk (CD-ROM), external control pad
Active display area (W x H)	527.04 x 296.46 mm
Weight	5.8 kg
Height	347 mm
Width	575 mm
Depth	42.5 mm
Glass protection	Yes
Compliance certificates	CB, CE, cULus, REACH, RoHS, WEEE
Certification	CB, CE, TÜV-Bauart, CU, cULus
User controls	picture (contrast, brightness, H. position, V. position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (timeout, position, H. position, V. position, touch switch), option (reset, language, source select, display mode, factory)
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select, Power
Supplied AC adapter type	AC


Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------


Matmenys ir svoris

Matmenys (I x P x A)	68,00cm x 45,00cm x 14,00cm
Svoris	8,25kg

Energijos efektyvumas ir ekologinis projektavimas


Energijos efektyvumo klasė **E** A-G

- › [Energijos etiketė](#)
- › [Gaminio informacijos lapas](#)
- › [EPREL duomenų bazė](#)



Dokumentai ir vaizdo įrašai

> [Vaizdo įrašas](#) youtube.com/watch?v=wI5bmhGWbo4

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt