

iiyama ProLite X2792HSU-B1 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black

Gamintojas: IIYAMA · Modelis: X2792HSU-B1 · EAN: 4948570126163 · Prekės kodas: 726937



144,90 €

Kaina su PVM

Be PVM: 119,75 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68.6 cm (27") Black
- ✓ Built-in speaker(s)
- ✓ HDMI HDMI version: 1.4 DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 120 Hz Response time: 3 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS
- ✓ Energy efficiency class (SDR): B ErP, TCO CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE



Aprašymas

The ProLite X2792HSU is a 27" Full HD monitor ideal for professionals who need more screen space, precise image quality, and a sustainable choice. Packaged without plastic and made from 85% post-consumer recycled materials, it meets TCO Certification and EPEAT Silver standards. Its IPS panel delivers sharp detail, vibrant colours and wide viewing angles, while the frameless design creates a sleek, distraction-free workspace. To take care of your eye health, it complies with the Eye Safe and Eye Comfort Certifications.

Techninė specifikacija

Specifications

Sandėlio grupė Flat Screens [+271][-238]

Display

Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	Full HD
Panel type	IPS
Response time	3 ms
Screen shape	Flat
Contrast ratio (typical)	1500:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
Display brightness (typical)	300 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Contrast ratio (dynamic)	80000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.311 x 0.311 mm
Horizontal scan range	30 - 140 kHz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.6 cm
DDC/CI	Yes
sRGB coverage (typical)	96%
NTSC coverage (typical)	72%

Performance

AMD FreeSync	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes

Multimedia

Built-in speaker(s)	Yes
---------------------	-----

Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Business
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	1
Number of downstream ports	2
USB Type-A downstream ports quantity	2
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort out version	1.2
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-4 - 20°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian, Ukrainian
Number of OSD languages	11
Power	
Energy efficiency class (SDR)	B
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	10.7 kWh

Power consumption (typical)	11.4 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	616.5 mm
Depth (with stand)	190 mm
Height (with stand)	436 mm
Weight (with stand)	3.9 kg
Packaging data	
Package width	688 mm
Package depth	124 mm
Package height	483 mm
Package weight	6.3 kg
USB cable length	1.5 m
Packaging content	
Cables included	AC, USB, HDMI
Quick start guide	Yes
HDMI cable length	1.5 m
Power cable length	1.5 m
Sustainability	
Sustainability certificates	ErP, TCO
Other features	
Packaging content	quick start guide, safety guide
Weight	3.9 kg
Height	436 mm
Width	616.5 mm
Depth	190 mm
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Certification	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS, ErP, WEEE, REACH, UKCA

User controls

picture adjust (brightness, contrast, ECO, ACR, OD, Adaptive Sync, X-Res Technology, DPS), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.), OSD settings (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI, display information), miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, audio settings (volume, mute), recall (recall all))

Control panel

Joystick: Center: Power/Menu, Up/Input Select, Down, Left/i-Style colour/Eco/Blue Light Reducer, Right/Volume/Mute Audio

Matmenys ir svoris

Matmenys (I × P × A)

70,00cm × 13,00cm × 48,00cm

Svoris

6,30kg