

iiyama ProLite XB3270QSU-B1 computer monitor 80 cm (31.5") 2560 x 1440 pixels Quad HD LED Black

Gamintojas: **IIYAMA** · Modelis: **XB3270QSU-B1** · EAN: **4948570123636** · Prekės kodas: **726944**



265,90 €

Kaina su PVM

Be PVM: **219,75 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 cm (31.5") Black
- ✓ Height adjustment 15 cm Built-in speaker(s)
- ✓ HDMI HDMI version: 2.0 DisplayPorts quantity: 1 DisplayPort version: 1.4
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 100 Hz Response time: 3 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 2560 x 1440 pixels Quad HD Panel type: IPS
- ✓ Energy efficiency class (SDR): E ErP CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE



Aprašymas

The ProLite XB3270QSU-B1 is a 31.5" screen featuring an IPS panel and QHD (2560x1440) resolution, delivering both excellent colour performance with wide viewing angles and noticeably sharper images, which is ideal for productivity solutions, demanding office and financial applications. The 150mm height-adjustable stand ensures you can adjust the screen position to your preferences, and the flicker-free panel with blue light reducer function reduces eye fatigue.

Techninė specifikacija

Specifications

Sandėlio grupė	Flat Screens [+271][-238]
----------------	---------------------------

Display

Display diagonal	80 cm (31.5")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	Quad HD
Panel type	IPS
Response time	3 ms
Screen shape	Flat
Contrast ratio (typical)	1200:1
Maximum refresh rate	100 Hz
Display number of colours	1.07 billion colours
Display brightness (typical)	250 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Aspect ratio	16:9
Contrast ratio (dynamic)	80000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.272 x 0.272 mm
Horizontal scan range	30 - 90 kHz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm
Colour depth	8 bit
sRGB coverage (typical)	100%
NTSC coverage (typical)	72%

Performance

NVIDIA G-SYNC	No
AMD FreeSync	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes

Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Business
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	3
Number of downstream ports	3
HDMI ports quantity	1
HDMI version	2
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone connectivity	3.5 mm
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	5 - 20°

On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, French, Italian, Japanese, Dutch, Polish, Russian
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	26.9 kWh
Energy consumption (HDR) per 1000 hours	0 kWh
Power consumption (typical)	35 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	726 mm
Depth (with stand)	239.5 mm
Height (with stand)	580 mm
Weight (with stand)	8.6 kg
Height (without stand)	440 mm
Packaging data	
Package width	810 mm
Package depth	176 mm
Package height	512 mm
Package weight	10.8 kg
Packaging content	
Cables included	AC, USB, HDMI
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
Packaging content	quick start guide, safety guide
Weight	8.6 kg
Width	726 mm

Depth	239.5 mm
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Certification	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
User controls	picture adjust (brightness, contrast, i-Style colour, ACR, Eco, OD, X-Res technology), colour settings (gamma, RGB range, colour temp.), image settings (video mode adjust, blue light reducer, sharp and soft), OSD (H. position, V. position, time, background, language), extra (reset, DDC/CI, LED, opening logo, Adaptive Sync, display information), input select (source), audio settings (volume, mute)
Control panel	Power, Menu, Up / Right / Volume, Down / Left / Eco, Input/ Exit
Matmenys ir svoris	
Matmenys (I × P × A)	81,00cm × 51,00cm × 18,00cm
Svoris	10,72kg