

iiyama ProLite T2238MSC-B1 computer monitor 54.6 cm (21.5") 1920 x 1080 pixels Full HD LED Touchscreen Black

Gamintojas: IIYAMA · Modelis: T2238MSC-B1 · EAN: 4948570122899 · Prekės kodas: 726949



482,90 €

Kaina su PVM

Be PVM: 399,09 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 54.6 cm (21.5") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Response time: 5 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS
- ✓ Energy efficiency class (SDR): D ErP REACH, RoHS, WEEE



Aprašymas

The Full HD (1920x1080) monitor ProLite T2238MSC-B1 with IPS panel technology offers exceptional colors and wide viewing angles. The Optical Bonded Projective Capacitive (PCAP) 10-point touch technology ensures a seamless and accurate touch response and a lower light reflection, in addition, the display is protected against humidity and potential moisture development. A robust metal housing and a scratch-resistant 7H edge-to-edge glass with anti-fingerprint coating make the monitor particularly suitable for integration in demanding environments. The monitor meets also a IPX1 protection rating, making it waterproof for a period of time against dripping water. The flexible stand can be positioned at several angles creating a comfortable and ergonomic user experience and the integrated cable management system hides all the cables and electrical wires giving a neat and cable-free workspace. The ProLite T2238MSC-B1 can be used in landscape, portrait and face-up orientation. A perfect solution for interactive signage, instore retail, POS and interactive presentations.

Techninė specifikacija

Specifications	
Sandėlio grupė	Flat Screens [+271][-238]
Display	
Display diagonal	54.6 cm (21.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Display brightness (peak)	600 cd/m²
Display brightness (typical)	600 cd/m²
Display brightness	525 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.249 x 0.249 mm
Horizontal scan range	30 - 83 kHz
Viewable size, horizontal	47.9 cm
Viewable size, vertical	26 cm
Display diagonal (metric)	54.5 cm
Surface hardness	7H
Performance	
Low Blue Light technology	Yes
Palm rejection	Yes
Multimedia	

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Office
Product colour	Black
Housing material	Metal
Front bezel colour	Black
Glass thickness	3.6 mm
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	2
USB Type-A downstream ports quantity	2
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
HDCP	Yes
AC (power) in	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, French, Japanese, Dutch, Polish, Russian
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	12.9 kWh
Power consumption (typical)	17 W
Power consumption (standby)	1.5 W

Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Weight & dimensions

Width (with stand)	512.5 mm
Depth (with stand)	239.5 mm
Height (with stand)	353.5 mm
Weight (with stand)	6.8 kg
Bezel width (side)	1.7 cm
Bezel width (top)	1.98 cm
Bezel width (bottom)	1.98 cm

Packaging data

Package width	625 mm
Package depth	150 mm
Package height	430 mm
Package weight	8.1 kg
Package type	Box

Packaging content

Cables included	AC, USB, HDMI
Quick start guide	Yes

Sustainability

Sustainability certificates	ErP
-----------------------------	-----

Other features

International Protection (IP) code	IP1X
Protection features	Waterproof
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Second display effective viewing area	479 x 260 mm
Brightness	525 cd/m²
Active display area (W x H)	479 x 260 mm
USB ports quantity	2
Weight	6.8 kg

Height	353.5 mm
Width	512.5 mm
Depth	239.5 mm
Compliance certificates	REACH, RoHS, WEEE
User controls	Picture adjust (brightness, contrast, i-Style color, adv. contrast, ECO mode, OD, X-Res), color settings (gamma, RGB range, color. temp.), image settings (video mode adjust, blue light reducer, sharp & soft), OSD (H. pos., V. pos., time, background, rotate, language, display information), extra (reset, DDC/CI, signal select, volume, mute, led, opening logo, touch switch)
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Eco, Scroll down/ Volume, Enter/ Input select, Power
Matmenys ir svoris	
Matmenys (I × P × A)	51,00cm × 24,00cm × 35,00cm
Svoris	6,80kg