



LTE Router
TRB140 No Wi-Fi
10/100/1000
Mbit/s Ethernet
LAN (RJ-45)
ports 1 Mesh
Support No MU-
MIMO No
2G/3G/4G
Antenna type 1
x SMA for LTE 1
x Virtual
network
interface via
micro USB 24
month(s)



Modelis: TRB140003000

Gamintojas: TELTONIKA

EAN: 4779027312408

Prekės kodas: 72695

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

131.99€

Gross depth (mm): 175 | Gross height (mm): 150 | Gross weight: 0.43 | Gross width (mm): 70.00 | Net weight: 0.307 | Packing quantity: 10 | Paper/Pasteboard: 123 | Tare weight (kg): 0.123 | Volume (m3): 0.0018375 | Embeeded battery: No | WEEE tax: Yes | WEE classification: CL109:6:2017-04-01 | Ethernet LAN data rates: 10/100/1000 | USB ports quantity: 1 x Virtual network interface via micro USB | Producer product name: TRB140 | Producer product family: LTE Router | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi band: No Wi-Fi | Software type: RutOS (OpenWrt based Linux OS) | Mesh Support: No | Mobile Broadband: 2G/3G/4G | MU-MiMO: No | Antenna type: 1 x SMA for LTE | Processor model: ARM Cortex-A7 1.2 GHz CPU | SFP+ ports quantity: 0 | Warranty: 24 | Internal memory: 128 MB (50 MB available for userspace) | Housing material: Aluminum | Operating relative humidity (H-H): 10 % to 90 % non-condensing | Dimensions (WxDxH): 74,5x64,4xx25 | Operating temperature (T-T): -40 °C to 75 °C | PoE in: Passive PoE over spare pairs. Possibility to power up through LAN port, not compatible with IEEE802.3af, 802.3at and 802.3bt standards | Input voltage: 9 - 30 VDC (4 pin industrial socket), reverse polarity protection, surge protection >33 VDC 10us max | Supported protocols: HTTP(S), MQTT, Azure MQTT, Kinesis | Firewall security: Pre-configured firewall rules can be enabled via the WebUI, unlimited firewall configuration via CLI; NAT; NAT-T | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, SMTP, SSL v3, TLS, PPP, PPPoE, SSH, DHCP, SNMP, MQTT, Wake on LAN (WOL) | Gross depth master carton: 375 | Gross width master carton: 370 | Gross height master carton: 170 | Net weight master carton: 4.3 | Tare weight master carton: 0.401 | Producer: Teltonika | Palette Qty: 730

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903