

iiyama ProLite XUB2797UHSNP-B1 computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LED Black

Gamintojas: IIYAMA · Modelis: XUB2797UHSNP-B1 · EAN: 4948570123810 · Prekės kodas: 726963



360,89 €

Kaina su PVM

Be PVM: 298,26 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68.6 cm (27") Black
- ✓ Height adjustment 15 cm Built-in speaker(s)
- ✓ USB upstream port type: USB Type-C HDMI HDMI version: 2.0 DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 60 Hz Response time: 4 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 3840 x 2160 pixels 4K Ultra HD Panel type: IPS
- ✓ Energy efficiency class (SDR): F ErP, TCO CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
- ✓ Warranty period: 5 year(s)



Aprašymas

Discover the XUB2797UHSNP, a 27" 4K IPS panel equipped with USB-C dock (96W PD), KVM switch, and RJ45 for LAN connectivity. The KVM switch allows to connect multiple computers through a single console. Get rid of cable clutter with the USB-C dock that carries all data (audio and video) whilst powering your notebook. Easily extend your desktop by creating a dual-monitor set-up with the DisplayPort output. Enjoy accurate colours and wide viewing angles thanks to the IPS panel. Benefit from exceptional performance for tasks like photography and web design, thanks to the 4K resolution and high contrast. The ergonomic stand offers a height adjustment of 150mm and tilt/swivel mechanisms for portrait mode, optimizing comfort while working with extensive data sheets

Techninė specifikacija

Specifications	
Sandėlio grupė	Flat Screens [+271][-238]
Display	
Display diagonal	68.6 cm (27")
Display resolution	3840 x 2160 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	4K Ultra HD
Panel type	IPS
Response time	4 ms
Screen shape	Flat
Contrast ratio (typical)	1300:1
Maximum refresh rate	60 Hz
Display number of colours	1.07 billion colours
Display brightness (typical)	350 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Contrast ratio (dynamic)	80000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.155 x 0.155 mm
Horizontal scan range	30 - 140 kHz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm
DDC/CI	Yes
Colour depth	8 bit
Colour gamut standard	NTSC, sRGB
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%
Performance	
Flicker-free technology	Yes

Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Business
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of downstream ports	4
Number of USB Type-C upstream ports quantity	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	96 W
HDMI ports quantity	1
HDMI version	2
DisplayPorts quantity	1
DisplayPort out quantity	1
DisplayPort out version	1.2
Built-in KVM switch	Yes
HDCP	Yes
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes

Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	23 - 5°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	26 kWh
Power consumption (typical)	33 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	614.5 mm
Depth (with stand)	209.5 mm
Height (with stand)	547.5 mm
Weight (with stand)	6.7 kg
Width (without stand)	614.5 mm
Depth (without stand)	209.5 mm
Height (without stand)	397.5 mm
Packaging data	
Package width	688 mm
Package depth	138 mm
Package height	463 mm
Package weight	9.2 kg
Package type	Box

Packaging content

Cables included	AC, USB, HDMI, DisplayPort, USB Type-C
Quick start guide	Yes

Sustainability

Sustainability certificates	ErP, TCO
-----------------------------	----------

Other features

Packaging content	quick start guide, safety guide
Weight	6.7 kg
Width	614.5 mm
Depth	209.5 mm
Warranty period	5 year(s)
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Manufacturer warranty	5 years (for details and eligible countries please check the Warranty section of our website)
Ethernet LAN (RJ-45) ports	1
User controls	picture adjust (brightness, contrast, Eco, ACR, OD, X-Res Technology, DPS), colour settings (6-Axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp., user preset), PiP/PbP (sub source, PiP position, PiP size, swap), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI, display information), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, LED, USB BC, MST, USB C, MAC Address), KVM, input select (source), audio settings (volume, mute, input)
Control panel	Joystick/Power: Up/Input Select, Down, Right/Volume/Mute, Left/Submenu / Shortcut, Input / Exit

Matmenys ir svoris

Matmenys (I × P × A)	69,00cm × 14,00cm × 46,00cm
Svoris	9,08kg